



DESIGN BY HOWE IN-HOUSE DESIGN TEAM 2011

HOWE.COM/USU

USU

Usu is value for money. It is the obvious choice for the price conscious customer who is still requiring simple aesthetics, space-saving attributes and ease of handling. It is developed for multi-usage canteen and training areas. The concealed castor solution and the chair hanger system adds even more to the ease of handling. The legs are folded in pairs by a simple and secure spring-handle and the sub frame can be used as carriage handle. The table's simple and elegant aesthetics make it compatible with other furniture styles.





DESCRIPTION

4-legged stackable folding table for multi-purpose canteen and training applications.

PRODUCT DETAILS

TABLETOPS

LAMINATE VERSION

Coloured laminate with 0.03" laminate on both sides. Total thickness of 0.69". Standard coloured laminates are black, white, and grey. Standard wood grain laminates are maple, cherry and walnut. Any Formica Colour System colour available upon request.

EDGES

Standard option is: 0.08" matching ABS edge on laminate tabletops.

BASES

ROUND TUBE: Legs in round steel tube $\varnothing 1.38"$ 0.98" gauge. Leg steel quality according to norm EN10305-3 and subframe according to DC01. Angled leg corners. Legs and mechanism in chrome (20 μ), or in Howe grey, white, black or alu grey powder coating. Subframe in white powder coating.


SQUARE TUBE: Legs in square steel tube 1.38" x 1.38" 0.98" mm gauge. Leg steel quality according to norm EN10305-3 and subframe according to DC01. Angled leg corners. Legs and mechanism in chrome (20 μ), or Howe grey, white, black or alu grey powder coating. Subframe in white powder coating.

GLIDES & CASTORS

As standard four adjustable glides $\varnothing 1.38"$ made of black nylon (PA6). Adjustable up to 1.18" height. Two mono-directional castors in black nylon (PA6) in glides on one end are optional (castors in grey TPE). Consealed castors optional.

MECHANISM

Folding mechanism in steel construction concealed under polyamide cover. Release handle in spring-managed steel rod. Legs folds in pairs. Built-in friction to prevent legs for folding out unintendedly.



STACKING CAPACITY

Folded tables have a folding depth of 4.9". Can be stacked vertically on short and long side.

DIMENSIONS AND WEIGHT

DIMENSIONS

The height of the table is 28.7". ADA table height is possible.

WEIGHT

48" x 30" rectangular table with laminate tabletop weighs 50.5 lb.

STANDARD SHAPES & SIZES

RECTANGLES:

48" x 24"

48" x 30"

60" x 30"

72" x 30"

Other sizes available, please contact HOWE a/s for further inquiries.

ACCESSORIES

CHAIR HANGER SYSTEM in chromed steel rod to be attached on subframe. Retro-fittable to tables with a width of 30". Single or double version. Double version for tables in 30" depth only.

MODESTY PANEL in 0.16" green shaded acrylic mounted on hooks. Attachable Panel height is 9.8".

BAG HANGER in chrome. Mounted on the width tube of the leg. Retrofittable. S-shaped, only for round legs.

LINKING BRACKETS in black PA6. For positioning the tables. Suitable for both round legs and square legs tables. Two brackets are recommended per table.



TABLE TRANSPORTER made of steel frame, type E235. Rubber profile for protection. Powder coated in HOWE grey colour. A-kit for rectangular tables and L-kit for all other shapes. The A-kit stores up to 10 tables, nested on short side. Nest top against top and base against base. 2 fixed wheels and 2 multidirectional wheels with brake. Safety straps to hold tables in place during transport. For tables with min. width of 21.6". Special, narrow transporter for tables with min. width of 17.7". Up to 1322,8 lb load. Delivered flat packed (pallet size). Easy assembled with 26-28 screws.

Dimensions for A-kit: Height: 44,5", length: 79,1", depth: 22"

Dimensions for L-kit: Height: 49,4", length: 79,1", depth: 30,5"

The dimensions are without tables on the transporter.

ERGONOMY & ENVIRONMENT

The Usu table is manageable for one person. With the castor versions no heavy lifts are required. All parts of the table can be dismantled and recycled.

Frame and mechanism consists of only steel elements plus polyamide components easy to dismantle.

TESTS

The Usu table has been subjected to the strength and durability tests EN 15372:2008, level 3, and ANSI/BIFMA X5.5. The table passed both without damages or signs of beginning damages.

WARRANTIES

HOWE a/s gives a 5 years guarantee on all Usu tables against weld breakages, defective material, workmanship and performance under normal use. For full information please see the warranty provision on howe.com.