HU35025 UNIVERSAL DIGITAL **PRESSURE TESTER**

NEW!

/Hubitools



MULTI-FUNCTIONAL

Replaces most pressure tester kits in just ONE set

Kit includes:

- Tester
 - 7" Color TFT display with resistive touch panel
 - Battery: LiPo 3,7V / 2000mA
 - USB smart battery charge with led indicator
 - PC connection by USB port
 - ABS enclosure with rubber bumper
 - Self-calibration
 - User-friendly touchscreen
 - Multilingual: English, Spanish and French
- Sensor: 0 to 300 Bars (0 to 4351 psi)
- Sensor -1 to 3 Bars (-14.5 to 43.5 psi)
- Universal Diesel Compression Adaptor - With this single innovative adaptor, allows technician to test 50+ applications
- Universal Gasoline Compression Adaptor
- Eight specific professional quick coupling adaptors
- Vacuum adaptors

DISPLAY

It's digital, so you can save, export, print and share the results!



- 7" Color TFT display with resistive touch panel
- Battery: LiPo 3,7V / 2000mA
- USB smart battery charge with led indicator
- PC connection by USB port
- ABS enclosure with rubber bumper (Hubitools design)
- All screws are mounted on brass inserts
- 1/4 thread brass insert at back to fix suction cup, etc...



Vacuum pressure

Fuel low pressure






AdBlue pressure





T ADAPTORS INCLUDED IN THE HU35025

- Plug and play
- Flexible



USE QUICK COUPLER TO FIT MOST OEM CONNECTIONS ON CARS!

ADAPTOR MITYVAC 2.0 HU35025-12

Get the electronic precision of 0.01bar while generating a pressure/vacuum with the Mityvac pump

APPLICATION EXAMPLE

- Vacuum test of the AdBlue tank's air vent
- Vacuum test of the throttle body
- Vacuum test of the vacuum hoses
- Vacuum or pressure test of airtightness of control systems of EGR (evap), turbo, Wastegate
- Vacuum or pressure test of any sensors (sensor removed from the car: comparing results between our tool and the OBD source)

COOLING SYSTEM ADAPTER

HU35025-13

- This adapter can be used either along with the other T adapters already included in the HU35025 or alone to perform a pressure test of the cooling system
- Its design reproduces the OEM connection allowing to connect in various spots in the cooling system (help locate an issue by bypassing some elements)
- Example of use, connect to the line that goes to: EGR coolant port, radiator pressure release port, controlled thermostat port, coolant reservoir port



MORE ADAPTORS AVAILABLE FOR THE PRESSURE TESTER

USE THE MITYVAC PUMP IN COMBINATION WITH THE HU35025 UNIVERSAL PRESSURE TESTER



GIVE YOUR PUMP A DIGITAL ACCURACY OF 0.01bar!

IDEAL ADAPTER TO TEST MODERN COOLING SYSTEM



Ex: Controlled Thermostat



SCHRADER ADAPTERS HU35025-14 / HU35025-15 / HU35025-16

- These adapters allow for fuel low pressure testing of engines using Schrader type connectors inlets for pressure testing. (Ford, GM, etc.)
- Also allow for cooling system pressure testing on cars equiped with schrader type coolant bleeding valve



7/16" X 20 UNF

HU35025-14



8V1

HU35025-15



MORE ADAPTORS AVAILABLE

M8X100

HU35025-16

FOR THE PRESSURE TESTER

Fuel pump



FSI pump



Cooling system


GASOLINE HIGH PRESSURE ADAPTERS HU35029

NEW


• This Kit allows, using the 0-300bars sensor included in the HU35025, to test the Gasoline High pressure of most popular gasoline (Petrol) engines (FSI, TFSI, TCe, T-Jet, Etc.) Both using the sensor location or the dedicated plug location

Kit includes the following adapters :

- HP1 = M12x150
- HP2 = M12x125
- HP3 = M14x150
- HP4 = M10x100
- HP5 = M8x100



of the sensor







NEW

EASILY & SAFELY TEST THE DIESEL COMMON RAIL PRESSURE

With this set, the technician will be able to safely test the diesel common rail pressure both in-line (in series with engine running) and for direct pump pressure (cranking the engine).

This kit provides all the hardware (special sensor, plugs, hoses) to perform a very precise and accurate test in conjunction with the HU35025 Universal Digital Pressure Tester. The hoses included in the kit will allow the technician to measure and diagnose most usual common rail applications.





Kit includes :

- 2000 Bars (29000 psi) Sensor
- Sensor plug for direct pump pressure
- 2x M12 x 150 hoses for most common applications
- Fuel capturing reservoir










PRESSURE IN LINE



LAST GENERATION DIESEL ADAPTERS

HU35028

- This set, in association with the HU35026 will allow to test the diesel high pressure of most popular carsin the market. (Delphi, Siemens, Bosch and Denso pumps)
- One end of the adapters always has a M12x150 thread to fit our hoses.

The other ends are:

- M12x125 (2x)
- M14x150 (2x)
- M14x100 (1x)
- M16x100 (1x)


COMMON RAIL DUMMY REGULATOR SET HU35031

- This set, used in association with HU35026, will allow to bypass the pump's regulator and measure the pressure to diagnose any regulator or pump issue
- After observing the weak pump pressure : Simply remove the regulator, and choose the right dummy plug to bypass and seal the port. If the pressure comes back to normal, the regulator causes the loss of pressure. If the pressure stays too low, the pump is defective. This test is recommended by manufacturer of high pressure pumps
- Kit includes 8 different dummy to seal any regulator ports


COMMON RAIL CAPS SET

HU35030

- Used in association with HU35026, this set will allow to close injectors fuel inlet directly on the common rail. The purpose of this operation is to identify if an injector is leaking or not
- Works for 3, 4, 5 and 6 cylinders engines
- Kit includes 6x M12x150 plugs and 6x M14x150 plugs











For more information:



ANSED Diagnostic Solutions LLC 1528 Walnut Street Suite 1600 Philadelphia, PA 19102 888.685.7287

sales@anseddiagnostics.com www.anseddiagnostics.com

©ANSED Diagnostic Solutions LLC. All rights reserved. Form: HU35025/ENG/v1.0