



SBC635MCMTWIN



33.5" x 23.63" x 25" (H x W x D)

Dual tap coffee dispenser in black, with a combination nitro/flat coffee tap kit in stainless steel

Highlights:

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro-infused cold brew drafts

Digital thermostat lets you set the perfect temperature for any cold brew

Automatic defrost ensures minimum user maintenance

Product Features:

| | |
|--|---|
| Dispenses both flat and nitro-infused coffee | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro-infused drafts from two cornelius kegs |
| Complete tap kit | Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs |
| Automatic defrost | Reduced user maintenance with auto defrost operation |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit |
| Ideal temperature | Operates between 33° and 50°F to keep your coffee stored at just the right serving temperature |
| Fully finished black cabinet | Allows the dispenser to be used freestanding |
| Reversible door | User-reversible door swing for added flexibility |
| Casters included (ships unassembled) | To make the unit portable, install this set of 2 1/2" high locking casters |
| Top guard rail (ships unassembled) | Attractive chrome guard rail helps to reduce spills and neaten service |



SBC635MCMTWIN Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 33.5" (85 cm) |
| Width | 23.63" (60 cm) |
| Width with Door Open | 25.0" (64 cm) |
| Depth | 25.0" (64 cm) |
| Depth with door at 90° | 47.0" (119 cm) |
| Capacity | 5.6 cu.ft. (159 L) |
| Defrost Type | Automatic |
| Door | Black |
| Cabinet | Black |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Energy Usage/Year | 310.0kWh/year |
| Amps | 0.86 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 80.0 lbs. (36 kg) |
| Shipping Weight | 83.0 lbs. (38 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Keerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Height with Tap | 49.0" (124 cm) |
| Number of Taps | 2 |
| Thermostat Type | Digital |
| Refrigerant | R600a |
| Refrigerant Amount | 1.13 oz. |
| High Side PSI | 250.0 |
| Low Side PSI | 110.0 |
| Inter Height | 28.0" (71 cm) |
| Interior Width | 20.5" (52 cm) |
| Interior Depth | 19.0" (48 cm) |
| Compressor Step Height | 8.25" (21 cm) |
| Wheel Qty | 4 |
| Temperature Range | 33° to 50° F |

