

# SBC635MOS7NKHH



#### 33.5" x 24" x 25.88" (H x W x D)

Freestanding commercially listed outdoor beer dispenser, auto defrost with digital thermostat, stainless steel wrapped exterior, and horizontal handle; no tapping equipment included

#### **Highlights:**

Commercially listed to NSF-7 standards and meets UL-471 Weatherproof construction allows safe use in the outdoors Full-sized capacity to hold half, quarter, 1/6 or mini kegs

### **Product Features:**

Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments	
Outdoor beer dispenser	Meets UL guidelines for use in the outdoors, with weatherproof construction and a sealed back	
Full-sized	Large 5.6 cu.ft. interior accepts half, quarter, and mini kegs	
Stainless steel wrapped exterior	Weatherproof construction on the exterior cabinet, door, and top	
Professional handle	Brushed stainless steel handle with a thin 14mm diameter is mounted horizontally across the door for a sleek look	
Digital thermostat	Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit	
Automatic defrost	Reduced user maintenance with auto defrost operation	
Ideal beer temperature	Operates between 33 <sup>o</sup> and 50 <sup>o</sup> F to keep a variety of beers stored at just the right serving temperature	
Ground Fault Circuit Interrupter	Our integrated GFCI exceeds U.L. requirements for safety by protecting your unit from shocks and circuit breaks	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com





## SBC635MOS7NKHH Specifications:

Overview		
Height of Cabinet	33.5" (85 cm)	
Width	24.0" (61 cm)	
Width with Door Open	25.25" (64 cm)	
Depth	25.88" (66 cm)	
Depth with door at 90°	47.0" (119 cm)	
Capacity	5.6 cu.ft. (159 L)	
Defrost Type	Automatic	
Door	Stainless Steel	
Cabinet	Stainless Steel	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Amps	0.86	
Voltage/Frequency	115 V AC/60 Hz	
Weight	150.0 lbs. (68 kg)	
Shipping Weight	157.0 lbs. (71 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
Kegerator		
Door Swing	RHD	
Reversible	Yes	
Thermostat Type	Digital	
Refrigerant	R600a	
Refrigerant Amount	1.13 oz.	
High Side PSI	250.0	
Low Side PSI	110.0	
Inter Height	28.0" (71 cm)	
Interior Width	20.5" (52 cm)	
Interior Depth	19.0" (48 cm)	
Wheel Qty	4	
Surface	Stainless Steel	
Temperature Range	33º to 50º F	



