

Product Safety:

www.spotlessmaterials.com/product-safety

In case of poisoning, call your Poison Center at
1-800-222-1222 or go to poisonhelp.org

spotLESS Materials Inc.
200 Innovation Blvd.
State College, PA 16803
USA

spot | LESS™
M A T E R I A L S

HOME COLLECTION
APPLICATION GUIDE

DO NOT DISCARD INSERT

TOILET COATING

1. Clean toilet as you normally would.
2. Let the part of the bowl above the water line, completely dry or use a paper towel.
3. Shake product well before use.
4. Spray coating above the water line.
5. Wait 15 minutes before using the toilet as usual.

Pro Tips

- If you have hard water stains, clean first with a hard water remover.
- For best results, turn off toilet water supply, and flush one time to drain most of the water in the bowl. Once the surface is completely dry, apply coating and wait 5 minutes. Turn on water supply and use as normal.
- For bowl exterior, spray coating directly onto a paper towel and wipe toilet bowl rim and exterior surfaces prone to fouling and staining.

SINK & FIXTURE COATING

1. Clean the surface as usual.
2. Dry surface with a paper towel or cloth.
3. Shake product well before use.
4. Spray coating to cover entire surface.
5. Wipe with a cloth to spread evenly.
6. Wait 5 minutes before using as usual.

GLASS & MIRROR COATING

1. Clean the surface as usual.
2. Dry surface with a paper towel or cloth.
3. Shake product well before use.
4. Spray coating to cover entire surface.
5. Wipe with a cloth to spread evenly.
6. Wait 5 minutes before using as usual.

Pro Tips

- Any extra haze can be removed with glass cleaner or rubbing alcohol.