

Technical Documentation

CJM01525

Optim JM | AEHH8N_JM

Date: April 14, 2021

	
	Date: April 14, 2021

Technical Data Sheet

Motor Type: AEHH8N_JM	Catalogue No: CJM01525
-----------------------	------------------------

Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
15	2	3525	254JM	575	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.15	Continuous	B	-40 to 40°C °C	<1000 m

Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
92.40	91.00	92.40	91.70	91.50	90.50	86.00
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
22.34	210	180	270	3.0	13.3	92.80
NEMA KVA Code	Inertia (WR ²)			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft ²)	NEMA Load (lb-ft ²)	Max. Allowable (lb-ft ²)	Cold	Hot	
G	1.088	16.00	41.00	17	12	73.0

VFD Duty Information

Speed Range			VFD		S.F.
Constant Torque	Variable Torque	Constant Power	Carrier	Type	
6-60Hz	3-60Hz	60-90Hz	0	VPWM or CPWM	1.0 Only

Hazardous Locations Information

CSA Certified
Class I, Div 2, Groups B, C & D Class I, Zone 2, Groups IIB+H2, IIB & IIA
Temp Code (Sinewave / VFD)
T3C / T3B

Additional Certifications

Other Certification

Additional Information


Bearings		Approx. Weight
DE	NDE	lbs
6309ZZ	6307ZZ	301

Nameplate Drawing

Optim JM

TYPE	AEHH8N_JM		CAT. NO.	CJM01525		
OUTPUT	15 HP 11.19 kW		FRAME	254JM	TEFC	
R.P.M.	3525		POLE	2	INS.	F
VOLTS	575		PHASE	3	Hz	60
AMPS	13.3		CODE	G	S.F.	1.15
AMBIENT	40 °C		NOM. EFF. 92.40		MIN. EFF. 91.00	
BEARINGS	6309ZZ / 6307ZZ				RATING Cont.	
SER. NO.	TBD		DESIGN	B	WT. 301 LBS	
PWM VFD DUTY	VT	CT	CP		S.F.	
	3-60Hz	6-60Hz	60-90Hz		1.0 Only	

Connection Diagram




3 LEAD		SINGLE VOLTAGE			DELTA
VOLTAGE	CONN.	L1	L2	L3	
-	DELTA	1	2	3	

WD_3D

Thermal Limit Curves

Motor Type: AEHH8N_JM		Catalogue No: CJM01525		Family: Optim JM	
HP	15	Safe Stall Time		Full Load A	13.3 A
Voltage	575V 60Hz	Hot	12 s	% Inrush	698 %
RPM	3600	Cold	17 s	Locked Rotor A	92.80 A



T-N and I-N Curves

Motor Type: AEHH8N_JM		Catalogue No: CJM01525		Family: Optim JM	
HP	15	Full Load T	22.34 lb-ft	Full Load A	13.3 A
Voltage	575V 60Hz	Locked Rotor T	210 %	Locked Rotor A	92.8 A
RPM	3600	Pull Up T	180 %	Break Down T	270 %

