

Uniview 16 Channel with 8 PoE Ports Network Video Recorder



Features:

- 16-channel input
- Third-party IP cameras supported with ONVIF conformance
- Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- Up to 12 Megapixels resolution recording
- Support H.265/H.264 video formats
- Accurate retrieval, instant playback
- Up to 8TB for each disk
- Support various VCA detection alarm and VCA search
- Plug & Play with 8 independent PoE network interfaces
- Support for P2P, UPnP, NTP, DHCP, PPPoE
- Support for mobile client access

Video and Audio	
IP Video Input	16-ch
Two-way audio input	1-ch, RCA
Network	
Incoming Bandwidth	160Mbps
Outgoing Bandwidth	320Mbps
Remote Connection	128
Video/Audio Output	
HDMI/VGA	VGA:
HDMI/VGA Output	1920x1080P / 60Hz, 1920x1080P / 50Hz, 1600x1200 / 60Hz, 1280x1024 / 60Hz, 1280x720 / 60Hz, 1024x768 / 60Hz HDMI: 4K (3840x2160) / 60Hz, 4K (3840x2160) / 30Hz, 1920x1080P / 60Hz, 1920x1080P / 50Hz, 1600x1200 / 60Hz, 1280x1024 / 60Hz, 1280x720 / 60Hz, 1024x768 / 60Hz
Audio Output	1-ch, RCA
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Decoding	
Compression	H.265/H.264
Live View/ Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	4 x 12MP @ 20, 4 x 4K @ 30, 8 x 4MP @ 20, 16 x 1080P @ 25
Hard Disk	
SATA	2 SATA interfaces
Capacity	up to 8TB for each disk
External Interface	
Network Interface	21 RJ-45 10M/100M/1000M, self-adaptive Ethernet Interfaces
Network Function	HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, IP Server, P2P
Serial Interface	1 x RS-485
USB Interface	Front Panel: 1 x USB 2.0. Rear Panel: 1 x USB 3.0
Alarm In	4-ch
Alarm out	1-ch
General	
Power Supply	100 ~ 240 VAC
Consumption (without HDD)	≤ 20W
PoE	Max 30W for Single Port Max 240W Total (15W for Each)
Working Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
Working Humidity	10%~ 90%
Dimensions	380mm x 315mm x 46mm
Weight (without HDD)	≤ 2.4Kg (5.34lb)