

Uniview IP 4MP WDR Network IR Mini Bullet Camera

Features:

- 4MP Progressive SCAN CMOS Image Sensor
- 3.6mm Fixed Lens
- H.265 / H.264 / MJPEG Video Compression
- Triple Stream Encoding
- Smart IR, up to 30m IR distance
- 9:16 Corridor Format Option
- True 120dB Wide Dynamic Range
- ONVIF Conformance
- IP66 Ingress Protection Rating



Camera	
Sensor	1/3", 4.0 megapixel, progressive scan CMOS
Lens	3.6mm@F1.8
Shutter	Auto/Manual, 1/6~1/8000 s
Min. Illumination	Color: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 30m (98 ft) IR Range
S/N	>55dB
WDR	120dB
Noise Reduction	2D/3D

Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, SIP, QoS
Compatible Integration	ONVIF, API

Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet

Video	
Max Resolution	2592x1520
Video Compression	H.265/H2.64/MJPEG
Frame Rate	4MP (2592x1520): Max 20 fps; 4MP (2560x1440): Max 25 fps 3MP (2048x1520): Max 30 fps; 1080P (1920x1080): Max 30 fps
Video Streaming	Triple
9:16 Corridor Mode	Supported
ROI	Supported
OSD	Up to 8 OSDs
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas

General	
Power	12 V DC, or PoE (IEEE802.3 af)
	Power Consumption: Max 6.4 W
Dimensions (L x W x H)	157.3 x 62.4 x 63mm (6.2" x 2.5" x 2.5")
Weight	0.45 kg (0.99 lb)
Working Environment	-35°C ~ + 60°C (-31°F ~ 140°F), Humidity ≤ 95% RH (non-condensing)
Ingress Protection	IP66