

Uniview IP 4MP Network IR 2.8mm Fixed Eyeball Camera

Features:

- Day/night functionality
- Up to 120 dB WDR (Wide Dynamic Range)
- Smart IR, up to 30m (98 ft) IR distance
- H.265 / H.264 / MJPEG
- Triple Stream
- 9:16 Corridor Format
- ONVIF Conformance
- Wide Temperature range: -35°C to 60°C (-31°F to 140°F)
- Wide Voltage Range ±25%
- 4 KV surge protection designed for network interface
- IP66



Camera	
Sensor	1/3", 4.0 megapixel, progressive scan CMOS
Lens	2.8mm@F1.8
	Angle of view(H): 77.6°
Shutter	Auto/Manual, 1/6~1/8000 s
Min. Illumination	Color: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 30m (98 ft) IR Range
AWB (Auto white Balance)	Auto/Manual
Gain Control	Auto/Manual
WDR	120dB
Noise Reduction	2D/3D

Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, SIP, QoS
Compatible Integration	ONVIF, API

Interface	
Network	10M/100M Base-TX Ethernet

Video	
Max Resolution	2592x1520
Video Compression	H.265/H.2.64/MJPEG
Frame Rate	"4MP (2592x1520): Max 20 fps; 4MP (2560x1440): Max 25 fps 3MP (2048x1520): Max 30 fps; 1080P (1920x1080): Max 30 fps"
Video Streaming	Triple
9:16 Corridor Mode	Supported
OSD	Up to 8 OSDs
Motion Detection	Up to 2 areas
Privacy Mask	Up to 4 areas

General	
Power	12 V DC, or PoE (IEEE802.3 af)
	Power Consumption: Max 5.5 W
Dimensions (Ø x H)	Φ126 x 94 mm (Ø5.0" x 3.7")
Weight	0.45 kg (0.99 lb)
Working Environment	-35°C ~ + 60°C (-31°F ~ 140°F), Humidity ≤ 95% RH (non-condensing)
Ingress Protection	IP66