

## Performance Data for the Pure Spout PS-01 Filtration System

Model	Replacement	Rated flow	Rated capacity	Operating pressure range	Operating temp. range
PS-01	PSF-10	0.5 gpm (1.9 lpm)	300 gallons (1135 liters)	40 – 100 psi (2.7 – 6.9 bar)	35 – 100°F (2-38°C)



The Pure Spout PS-01 filtration system has been certified by IAPMO R&T against NSF/ANSI standard 53 for lead reduction.

This system has been tested according to NSF/ANSI 53 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 53 and verified and substantiated by test data.

## NSF/ANSI Standard 53

Substance	Influent Challenge Concentration	Maximum Permissible Product Water Concentration	Average % Reduction
Lead pH 6.5	0.15 mg/L ± 10% mg/L	0.005 mg/L	>99.9 %
Lead pH 8.5	0.15 mg/L ± 10% mg/L	0.005 mg/L	>99.9 %

Not all water will contain contaminants listed. Testing performed under standard laboratory conditions; actual performance may vary. Filter usage must comply with all state and local laws. Filter is only to be used with cold water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

See installation guide for general installation conditions and needs as well as manufacturer's limited warranty.