

MOBILELOCK™

DS530 Solar Charger

NOTE: This product works only with the DS600 Mobilelock

Product Function

The MOBILELOCK™ DS530 Solar Charger helps to keep your DS600 Mobilelock fully charged. First, fully charge your DS600 Mobilelock using the 120v Mobilelock power adaptor plugged into an outlet (charging a DS600 only from the DS530 solar charger may take several days). Mount the DS530 in a location that has optimal sun. There are four pieces of tape and four holes in the aluminum frame to be used for mounting. When using tape, make sure that the mounting surface is clean from wax, dirt and is dry. Test to make sure mounting is secure.

NOTE: The mounting tape is high bond type and may ruin the mounting surface in the event it is removed.

Once mounted plug the mini-DIN (round 7 pin) power connector into the charge port on the DS600. Make sure the “Charger Removed” notification is unchecked on the website. It is recommended to also uncheck the “Full Charge” alert on the website as it may result in multiple full charge notifications per day.

Although the charger is made for the sun, please do not expose your DS530 to extreme temperatures beyond the outdoor temperature. Rain, snow and humidity will not harm it.

Specifications:

Output: 5V

Solar Panel: 10W

Product Dimensions: 13.26 in x 8.03 in x 0.7 in

Product Weight: 2.5 lbs

Full One Year Warranty

The DS530 Mobilelock Solar Charger is warranted for one year from date of purchase. We will repair, without charge, any defects due to faulty materials or workmanship. For warranty repair information visit www.dewaltmobilelock.com or email us at info@dewaltmobilelock.com. This warranty does not apply to damage caused by negligent use or where repairs have been made or attempted by others. This warranty gives you specific legal rights and you may have other rights in certain states or provinces.