

Braille GREEN-LiTE Lithium Technology

Lighter. Stronger. Faster.

Part Number: G9



- Up to 5X More Stored Energy
- Easy Install: Built in a Direct Replacement Size
- Safe: Sealed Safe Design, LiFePO4 cylindrical cells, Internal fuse
- Fast Power: Rapid Recharge, Stable Voltage Output
- Greener: Modular Design For Longer Life
- Exclusive Braille Lithium Racing Warranty

PHYSICAL SPECS

Battery Sizing Class: "TX-9" Grouping
 Length: 5.9" / 150 mm
 Width: 2.57" / 65 mm
 Height: 3.58" / 91 mm
 Minimum Weight: 2.1 lbs / .95 kg
 Post Type: High Amperage Brass with 6mm x 1.0 mm Threaded Bolt
 Polarity: Right Side Negative (**G9L** available for Left)

PERFORMANCE

Voltage: 12 volts
 Full Charge Range: 13.8 volts
 Pulse Cranking Amps: 346
 Lead-Acid Equivalent Capacity: 18 LAH

CHARGING

Alternator or Mag: Minimum 14.0 volt output at 2 amp
 Battery charger: Braille Model # 1236L – 6amp Lithium
 Rapid Recharge: 6 AH electronically controlled
 Recommended Charge Voltage: 14.4 - 14.8 Volts
 Do Not Exceed Charge Voltage: Up to 15.25 Volts
 Minimum Recommended Voltage: 8.0 Volts

WARRANTY

Warranty: 2 Year Repair/Replacement

REPLACEMENT GUIDE

| Part # | Length | width | height | weight | Amp hr | Terminals |
|----------|--------|-------|--------|--------|--------|-----------|
| YTX9-BS | 5.90" | 3.43" | 4.13" | 5.0 | 8 | 2 |
| PTX9-BS | 6.00" | 3.44" | 4.19" | 5.9 | 8 | 2 |
| X2-9 | 5.88" | 3.44" | 4.19" | 6.3 | 8 | 2 |
| 9-BS | 5.88" | 3.44" | 4.13" | 8.0 | 8 | 2 |
| GTX9-BS | 6.00" | 3.44" | 4.19" | 8.6 | 8 | 2 |
| M329BS | 6.00" | 3.44" | 4.19" | 6.2 | 8 | 2 |
| 740-1825 | 5.98" | 3.42" | 4.17" | 7.1 | 8 | 2 |
| 44025 | 6.00" | 3.44" | 4.19" | 7.3 | 9 | 2 |



Braille Model G9 shown



braille
BATTERY
LIGHTER • STRONGER • FASTER

*Performance specifications denote maximum lead-acid equivalents.

Actual performance may vary. Pricing, specifications and features current as of 1/14, subject to change without notice. For latest information, contact Braille directly.