

CORE Elite 3 SPECIFICATIONS

STEP THROUGH ELECTRIC BIKE

FRAMESET	
FRAME	Hydroformed 6061 Aluminum step through ERGOFIT frame with smooth welds. Fender/rack mounts, internal cable routing, Electronic Access Port. Removable integrated battery with security lock.
COLOR	Matte Grey/Silver
FORK	SUNTOUR NEX eBike rated suspension with lockout
DRIVETRAIN	
SHIFTERS	SHIMANO 8-speed Rapidfire shift
CHAINRINGS	42T
CHAIN	KMC X8
REAR DERAILLEUR	SHIMANO ALTUS 8-speed
CASSETTE	8-speed 11-34T
COMPONENTS	
HANDLEBAR	Alloy ERGOFIT touring bar
GRIPS	VELO ergonomic grip
STEM	PROMAX toolless adjustable threadless
SEAT POST	PROMAX alloy 30.4mm with quick release (350mm)
SADDLE	SELLE ROYAL Nuvola - black
BRAKE LEVERS	TEKTRO ARIES
BRAKE CALIPERS	TEKTRO ARIES mechanical disc
ROTORS	180mm
WHEELS	
TIRES	MAXXIS Re-Volt 700x47C, 28"x1.75" with SilkShield bead-to-bead puncture protection
RIMS	iGO 700C dual wall alloy
ACCESSORIES	
INCLUDED	Front & Rear LED Lights (powered by main battery) Front Rack Mount for Light Front & Rear Cargo Rack Front & Rear Fenders Rear Bungee Straps Chain Guard Water Bottle Boss on Seat Tube

ELECTRIC TECHNOLOGY

DISPLAY UNIT	LCD Backlit, Main Power, USB charging Port, Diagnostic, Battery Status, Light Switch, Power-assist Level Selector,
	Walk Assist Control, Speedometer, Max Speed, Avg Speed, Odometer, Trip Timer
MOTOR	500W geared brushless hi-torque rear hub motor
TORQUE	up to 48Nm
CONTROLLER	48V, 18A
BATTERY TYPE	3200mAh Lithium-Ion removable battery
VOLTAGE	48V
BATTERY Ah	12Ah
BATTERY CAPACITY	576Wh
RANGE	75km (47mi) *
POWER ASSIST	9 Levels of power assisted pedaling
THROTTLE	Any time on demand thumb throttle
SENSOR	Electronic 32 pulse Cadence Sensor Integrated into the bottom bracket
CLASS	Class 2 **
BATTERY CHARGER	110/220V Smart charger, LED status, CUL, 2A
NOTES	
FRAME SIZE	ERGOFIT frame accommodates a rider from 5' to over 6'2"
SEAT HEIGHT (MIN/MAX)	80cm / 100cm (31.5" / 39.5")
BIKE WEIGHT	23.7kg (52.2 lbs)
BATTERY WEIGHT	3.3kg (7.3 lbs)
WEIGHT CAPACITY	114 kg (250 lbs)

^{*}Actual range may vary depending on Ah of battery rider weight and other riding conditions.

**electric Dike Class requiation:
Class 1 - Pedal assist motor with maximum assisted speed 32km/h (20mph)
Class 2 - Pedal assist motor and throttle with maximum assisted speed 32km/h (20mph)
Class 3 - Throttle and/or pedal assist motor with maximum assisted speed 45km/h (28mph)
all classes allow a maximum motor power of 750W(US) or 500W(Canada)

This bike is sold factory configured to CLASS 2 specifications.

Kickstand

Wellgo Pedals Tool Kit Battery Charger

^{**}electric bike class regulation:

