

Ultra-Strong Bond to PVC Panel and Pipes

WM2079



Description

WALLMASTER PVC-3 Primer is a water-based bonding primer specifically designed for adhesion to PVC panel, pipes, formwork and guttering. The primer is an adhesion-promoted product that provides outstanding adhesion to the PVC surface and ensures strong inter-coat adhesion with any water based acrylic paints.

PVC-3 Primer is a clear primer finish that can be applied by roller, brush or spray and can be top coated with most acrylic paints and texture finishes.

Principal Uses

PVC formwork, Panels, guttering, facias, siding and pipes. Do not use this product for any other purpose than as specified in our literature.

Recommended Topcoats

Wallmaster WeatherPlus Low Sheen, Matt, Semi-Gloss or Gloss. All Astec Armatex Trowel or Roll applied texture finishes.

Features

Australian Made and Owned

Astec Paints are an Australian owned and operated company that has been manufacturing premium finishes for the building and home restoration industries since 1978. For over four decades we have produced our entire product range in our South Australian plant. We are proud of what we make and that our products can carry the Australian Made and Owned Logo.



Technical Data

Clean-up	Water
Coverage	Up to 12 m ² /litre, surface dependant. Spread rate will be lower on rough surfaces.
Volume Solids.	41%
Recoat Time	Touch dry 30 minutes Recoat 4 hours
Gloss Level	75 @ 60 degrees
V.O.C	<38 gL

Application Data

Application

Stir well before use with a flat paddle or with a metal paint wacker using an up and down scooping action. Apply one coat Wallmaster PVC-3 Primer. For best results use a new unused 4 to 10 mm micro fibre roller cover. Remember, worn roller covers will produce a poor result. Brush application is best achieved with a synthetic trim brush. NOTE: Do not apply to surfaces that have had wax or silicone-based materials previously applied. Do not apply when ambient temperature is below 10°C or above 35°C or when humidity is very high.

Surface Preparation

New Unpainted PVC

All surfaces must be clean, dry and free of contaminants. Remove all dirt, dust and grease with a household detergent or sugar soap.

Mould Infested Areas

Wash down using a stiff brush with Sodium Hypochlorite (Chlorine) or a household bleach and water to remove the mould. Rinse off well with water and allow to dry. Apply one coat of Wallmaster PCV Primer to the entire surface.

Paint Disposal

Do not pour left over paint down the drain. Brush any leftover paint onto newspaper and allow to dry in a well-ventilated area. Dispose of the dry paint via domestic waste disposal. Empty cans should be left open and allowed to dry then disposed of in accordance with your local recycling legislations.

Safety Direction

Keep out of reach of children, provide adequate ventilation during use and do not dispose of left-over paint in any drainage systems.

First Aid

Eye Contact

Irrigate continuously with water for fifteen minutes holding eyelids open. Seek Medical advice.

Swallowed

Contact a doctor or Poisons Information Centre immediately. Do not induce vomiting. Give a glass of water. If vomiting does occur, place victim's face downwards at low level to prevent vomit entering lungs. Contact Astec for the relevant Material Safety Data Sheet.

Disclaimer;

The technical data is based on data believed by Astec Paints to be true and accurate at the time of writing, however, no guarantee of accuracy is given or implied and is subject to change without notice. This information is given in good faith for the assistance of users. All warranties express or implied are excluded and Astec makes no representation as to the accuracy, completeness or otherwise of the technical data. Every person dealing with the product does so at their own risk and must make their own independent determination of suitability and compliance to ensure their proper use. Astec has no control over the condition under which the products are stored, handled, used or applied, therefore our recommendations do not amount to a legal warranty and Astec accepts no responsibility if the recommendations are not followed or complied with.