

Paint & Prime Low Sheen

EASY ALL-IN-ONE-SOLUTION

WM2040



- FOR BARE PLASTERBOARD & TIMBERS
- NO UNDERCOAT REQUIRED - COVERS DARK COLOURS
- PERFECT PREP COAT FOR TRIM ENAMELS

Description

WALLMASTER **Paint&Prime** is the all-in-one single product solution to use as a primer and finish coat on bare or painted plasterboard. It is also an ideal primer and undercoat for pre-primed MDF and most timber skirtings and doors before the application of a hard wearing Wallmaster Acrylic or Urethane Trim Enamel. It glides on evenly then levels to an ultra-smooth finish with an elegant look. The soft touch technology provides a silky-smooth surface that is soft to the touch yet with a solid feel. Mould and bacteria resistant technology is incorporated making it ideal for kitchens, bathrooms & the whole home. Wallmaster Paint & Prime provides a tough, long lasting finish which bonds extremely well to the surface, is low in odour and low in VOC.

Principal Uses

Interior, paper faced boards, pre primed MDF, plaster, fibrous plaster, cement sheet, masonry and brick. Do not use this product for any other purpose than as specified in our literature.

Features

Hard Wearing-With Excellent Washability

WALLMASTER **Paint&Prime** is a tough hard wearing and long-lasting finish for any interior wall. It provides a smooth and very non-abrasive finish that is easy to clean and wipe free most household stains.

Soft Touch Technology

The formula incorporates our soft touch technology where highly treated pigments provide a very smooth, nonabrasive and luxurious feel to the surface of the paint.

Smooth and Even to Apply

The product is very smooth and even to apply by brush or roller and has excellent surface grip during application. Brush and roller marks flow and level out evenly resulting in smooth and uniform cover.

Ultra-Strong Hiding Power & High Opacity Base Coat

Achieving a high-quality finish with any wall or trim painting project requires that thorough preparation be carried out. As part of this preparation, it is imperative that any distinct difference in surface colour is hidden before applying any topcoat finish. Old existing paints, flushing and or repair compounds, different substrate materials or where existing bright colours are present, all have the potential to grin through the finish coats if not properly hidden from sight.

WALLMASTER **Paint&Prime** used as the undercoat acts as a highly efficient undercoat that incorporates maximum levels of strong opacifying pigments which easily hides colour irregularities on the substrate. It delivers a solid, well adhered and highly opaque base coat with a uniform even colour that is ready to accept the direct application of final wall and trim finishes.

Low VOC-Low Odour

Meets the Australian Paint Approval Scheme low VOC targets.

Asthma & Allergy Friendly

The formulation is free of known desensitizers, formaldehyde generators and or odour masking agents.

Australian Made and Owned

Astec Paints are an Australian owned and operated company that has been manufacturing premium finishes for the building and home restoration industries since 1978. For over four decades we have produced our entire product range in our South Australian plant. We are proud of what we make and that our products can carry the Australian Made and Owned Logo.



Excellent fill of sanded flushing and pre-primed MDF

New flushing and spot repairs to paper faced boards or pre primed MDF that have been sanded during preparation are soft, highly porous and very absorbent substrates. Thorough priming of these surfaces reduces their suction, extends working times for topcoat application and ensures excellent topcoat adhesion is achieved.

WALLMASTER **Paint&Prime** has excellent binding capabilities and the substrate fill required to seal and prime new sanded flushing on paper faced wall boards and primed MDF skirtings and or architraves. It provides good gloss hold-out of the subsequent top coats and ensures a smooth uniform end result is achieved.

Technical Data

Clean-up	Water
Coverage	Up to 12 m ² /litre, surface dependant. Spread rate will be lower on rough and or absorbent surfaces.
Volume Solids.	44%
Recoat Time	Touch dry 30 minutes Recoat 4 hours
Gloss Level	5.2 @ 60 degrees
V.O.C	43 gL

Application Data

Application

Stir well before use with a flat paddle or with a metal paint wacker using an up and down scooping action. Apply one coat WALLMASTER **Paint&Prime**. For best results use a new, unused 10 to 12 mm synthetic roller cover and a high-quality synthetic brush. Remember, worn roller covers will produce a poor result. NOTE: the number of coats required to achieve full cover will depend on application technique and/or the underlying substrate colour. Do not apply to surfaces that have had wax or silicone-based materials previously applied. Do not apply when ambient temperature is below 10°C, above 35°C or when humidity is very high.

Surface Preparation

Previously Painted Interior Surfaces

All surfaces must be clean, dry and free of contaminants. Remove all dirt, dust and grease with a household detergent or sugar soap. Scrape off any loose or flaking paint from existing painted surfaces then sand any gloss or semi-gloss finishes to a dull flat finish. Any existing paint that exhibits a complete lack of adhesion should be entirely removed. Fill any cracks, holes or nail holes with a suitable filler. Sand smooth and completely remove dust. Apply one coat WALLMASTER **Paint&Prime** to the entire surface.

New Interior Unpainted Paper Faced Wallboards

Lightly sand any joints where necessary and brush down the surface to remove any dust. Apply one coat WALLMASTER **Paint&Prime** to the entire surface.

New Interior Unpainted Plaster and Fibrous Plaster

Brush down the surface to remove any dust. Apply one coat WALLMASTER **Paint&Prime** to the entire surface.

New Interior Unpainted Fibro Cement Sheet

Brush down the surface to remove any dust. Apply one coat WALLMASTER **Paint&Prime** to the entire surface.

New Interior Unpainted Masonry and Brick

Brush down the surface to remove any dust. Apply one coat WALLMASTER **Paint&Prime** to the entire surface.

New Interior MDF

Lightly sand, remove all dust and apply one coat WALLMASTER **Paint&Prime** to the entire surface.

New Tannin Rich Interior Timber

Lightly sand, remove all dust and apply one coat Wallmaster Multi-Block Primer to the entire surface.

Water Stained Timber and Paper Faced Wallboards

Brush down the surface to remove any dust. Apply one coat Wallmaster Multi-Block Primer to the entire surface.

Mould Infested Areas

Wash down using a stiff brush with Sodium Hypochlorite (Chlorine) or a household bleach and water to remove the mould. Rinse off well with water and allow to dry. Apply one coat Wallmaster Multi-Block Primer to the entire surface.

Paint Disposal

Do not pour left over paint down the drain. Brush any leftover paint onto newspaper and allow to dry in a well-ventilated area. Dispose of the dry paint via domestic waste disposal. Empty cans should be left open and allowed to dry then disposed of in accordance with your local recycling legislations.

Safety Direction

Keep out of reach of children, provide adequate ventilation during use and do not dispose of left-over paint in any drainage systems.

First Aid

Eye Contact

Irrigate continuously with water for fifteen minutes holding eyelids open. Seek Medical advice.

Swallowed

Contact a doctor or Poisons Information Centre immediately. Do not induce vomiting. Give a glass of water. If vomiting does occur, place victim's face downwards at low level to prevent vomit entering lungs. Contact Astec for the relevant Material Safety Data Sheet.

Disclaimer;

The technical data is based on data believed by Astec Paints to be true and accurate at the time of writing, however, no guarantee of accuracy is given or implied and is subject to change without notice. This information is given in good faith for the assistance of users. All warranties express or implied are excluded and Astec makes no representation as to the accuracy, completeness or otherwise of the technical data. Every person dealing with the product does so at their own risk and must make their own independent determination of suitability and compliance to ensure their proper use. Astec has no control over the condition under which the products are stored, handled, used or applied, therefore our recommendations do not amount to a legal warranty and Astec accepts no responsibility if the recommendations are not followed or complied with.