



Professional Acrylic Primer Undercoat Ecofresh

WM2077



Description

WALLMASTER Pro Acrylic Primer Undercoat Ecofresh is a very low VOC, low odour, ultra-premium, acrylic primer undercoat. It has superior hiding power, adhesion and surface fill especially when used on joint flushing and repairs of new paper-faced boards. The product glides on smooth and evenly during application and has excellent fill and pigment binding capacity of sanded fillers. The product provides a strongly adhered, high opacity base coat for good gloss hold-out of the subsequent finish coats. The product is fortified with unique flow, wetting and levelling agents that provide excellent ease in brush, roll or spray application, resulting in a smooth and uniform finish.

Principal Uses

Interior, paper faced boards, plaster, fibrous plaster, cement sheet, masonry and brick. Do not use this product for any other purpose than as specified in our literature.

Features

Ultra-Strong Hiding Power & High Opacity Base Coat

Wallmaster Professional Acrylic Primer Undercoat Ecofresh acts as a highly efficient undercoat that incorporates maximum levels of strong opacifying pigments which easily hides colour irregularities on the substrate. It delivers a solid, well adhered and highly opaque base coat with a uniform even colour that is ready to accept the direct application of final wall and trim finishes.

Superior Cover

The product is very smooth and even to apply by brush or roller and has excellent surface grip during application. Brush and roller marks flow and level out evenly resulting in excellent substrate hide and cover.

Excellent fill of sanded flushing and pre-primed MDF

New flushing and spot repairs to paper faced boards or pre primed MDF that have been sanded during preparation are soft, highly porous and very absorbent substrates. Thorough priming of these surfaces reduces their suction, extends working times for topcoat application and ensures excellent topcoat adhesion is achieved.

Pro Acrylic Primer Undercoat Ecofresh has excellent binding capabilities and the substrate fill required to seal and prime new sanded flushing on paper faced wall boards and primed MDF skirtings and or architraves. It provides good gloss hold-out of the subsequent top coats and ensures a smooth uniform end result is achieved.

Low Odour-Very Low VOC

Meets the Australian Paint Approval Scheme very low VOC targets of, (< 1 gl)

Asthma & Allergy Friendly

The formulation is free of known desensitizers, formaldehyde generators and or odour masking agents

Australian Made and Owned

Astec Paints are an Australian owned and operated company that has been manufacturing premium finishes for the building and home restoration industries since 1978. For over four decades we have produced our entire product range in our South Australian plant. We are proud of what we make and that our products can carry the Australian Made and Owned Logo.



Technical Data

Clean-up	Water
Coverage	Up to 14 m ² /litre, surface dependant. Spread rate will be lower on rough and or absorbent surfaces.
Volume Solids.	38%
Recoat Time	Touch dry in 30 minutes / Recoat 2 hours
Gloss Level	4.2 @ 60 degrees
V.O.C	<1 gL

Application Data

Application

Stir well before use with a flat paddle or with a metal paint wacker using an up and down scooping action. Apply two coats Professional Matt SPT 3 in 1. For best results use a new unused 10 to 12 mm synthetic roller cover. Remember, worn roller covers will produce a poor result. Note; the number of coats required to achieve full cover will depend on the primers and sealers used during preparation, application technique and / or the underlying substrate colour. NOTE: Do not apply to surfaces that have had wax or silicone-based materials previously applied. Do not apply when ambient temperature is below 10°C, above 35°C or when humidity is very high.

Surface Preparation

New Interior Unpainted Paper Faced Wallboards

Lightly sand any joints where necessary and brush down the surface to remove any dust. Apply one coat Professional Acrylic Primer Undercoat Ecofresh.

New Interior Unpainted Plaster and Fibrous Plaster

Brush down the surface to remove any dust. Apply one coat Wallmaster Multi-Block Primer Acrylic Undercoat to the entire surface.

New Interior Unpainted Fibro Cement Sheet

Brush down the surface to remove any dust. Apply one coat Professional Acrylic Primer Undercoat Ecofresh to the entire surface.

New Interior Unpainted Masonry and Brick

Brush down the surface to remove any dust. Apply one coat Professional Acrylic Primer Undercoat Ecofresh or Wallmaster Multi-Block Primer Sealer Undercoat to the entire surface.

New Interior MDF

Lightly sand, remove all dust & apply one coat Professional Acrylic Primer Undercoat Ecofresh or Wallmaster Multi-Block Primer Sealer Undercoat to the entire surface.

New Interior Timber

Lightly sand, remove all dust & apply one coat Wallmaster Multi-Block Primer Sealer Undercoat to the entire surface.

Water Stained Timber and Paper Faced Wallboards

Brush down the surface to remove any dust. Apply one coat Wallmaster Multi-Block Primer Sealer Undercoat to the entire surface.

Mould Infested Areas

Wash down using a stiff brush with a household bleach and water to remove the mould. Rinse off well with water and allow to dry. Apply one coat Wallmaster Multi-Block Primer Sealer Undercoat to the entire surface.

Paint Disposal

Do not pour left over paint down the drain. Brush any leftover paint onto newspaper and allow to dry in a well-ventilated area. Dispose of the dry paint via domestic waste disposal. Empty cans should be left open and allowed to dry then disposed of in accordance with your local recycling legislations.

Safety Direction

Keep out of reach of children, provide adequate ventilation during use and do not dispose of left-over paint in any drainage systems.

First Aid

Eye Contact

Irrigate continuously with water for fifteen minutes holding eyelids open. Seek Medical advice.

Swallowed

Contact a doctor or Poisons Information Centre immediately. Do not induce vomiting. Give a glass of water. If vomiting does occur, place victim's face downwards at low level to prevent vomit entering lungs. Contact Astec for the relevant Material Safety Data Sheet.

Disclaimer;

The technical data is based on data believed by Astec Paints to be true and accurate at the time of writing, however, no guarantee of accuracy is given or implied and is subject to change without notice. This information is given in good faith for the assistance of users. All warranties express or implied are excluded and Astec makes no representation as to the accuracy, completeness or otherwise of the technical data. Every person dealing with the product does so at their own risk and must make their own independent determination of suitability and compliance to ensure their proper use. Astec has no control over the condition under which the products are stored, handled, used or applied, therefore our recommendations do not amount to a legal warranty and Astec accepts no responsibility if the recommendations are not followed or complied with.