

## COOLER HOLDER ASSEMBLY INSTRUCTIONS

Jim's Accessory Products, Inc. 550 O'Byrne Avenue, Louisville, KY 40223 1-888-844-JIMS - www.junglejimsap.com

## Parts Breakdown

COOL-CB	C-Shaped Bracket	1
COOL-CHB	L-Shaped bracket w/ sticker	1
203	9mm HCS GR5 Z	2
307	9mm Hex Flange Nut Z	2
416	9mm Split Lockwasher Z	2
703	Polyweb Triglide Fastener	2
705	Snap Buckle-male & female end	1
201	9mm Machine Screw Z	2
313	9mm lock jam nut	2
717	30" web strap	2



1. Insert strap through right side of the cooler holder C bracket.



2. Pull strap so that both sides are even.

3. Insert only the right side of the strap through the right side of the plastic triglide.

4. Follow the same strap over and through the left side of the same plastic triglide.



## 5. Slide the tri-glide to the center of the strap.

6. Insert both ends of the strap through the left slot on the male buckle.

7. Insert both ends of the strap over and through the right slot of the male buckle.

9. Right side is now complete.

side of the tri-glide.

10. Repeat steps 1 – 7 for the left side. #7 will use the female buckle.

8. Insert both ends of the strap up and through the left side of the tri-glide.

(This is the same tri-glide you assembled in steps 3-5). Repeat through the right

11. Place L-shape bracket and once a suitable location is found, mark spot and drill. Use (2) 203's, (2) 416's and (2) 307's.

12. Attach the C-Bracket to the L shape bracket by using (2) 201's and (2) 313's.

13. Insert cooler on base and buckle straps. To adjust strap size, use triglides.

1-888-844-JIMS - www.junglejimsap.com









