

New

EKZT-1 SERIES – electric chain hoists with up to 500 kg load-carrying capacity

- ▶ Chain hoist suspended on load looks
- ▶ Overload protected by slip clutch
- ▶ Integrated operation limit switch
- ▶ Safe stowing of the chain through chain store supplied as standard
- ▶ Chain block controlled via control pendant



Available from 12/2018

Available from 12/2018

Model	EKZT 301-1	EKZT 501-1
Art. no.	6194503	6194505

Technical specifications	EKZT 301-1	EKZT 501-1
Load-carrying capacity	300 kg	500 kg
Stroke	3 m	3 m
Max. lifting speed	3 m/min.	2.8 m/min.
Length of cable, control unit	1.6 m	1.6 m
Number of chain strands	1	1
Supply voltage	230 V / 50 Hz	230 V / 50 Hz
Dimensions (L x W x H)	288 x 221 x 442 mm	382 x 176 x 600 mm
Weight	14.3 kg	18.5 kg

SW series – steel winch with safety crank for lifting, holding and lowering work with up to 10 t load-carrying capacity

- ▶ Anchor points on head and claw
- ▶ Low force application when lifting the load
- ▶ Lifting support housing with helical toothed gear rod
- ▶ Stable base for assured stability
- ▶ Safe and easy operation with two handles - also for easy transportation
- ▶ Space-saving storage and transport thanks to folding crank

Model	SW 30	SW 50	SW 100
Art. no.	6171203	6171205	6171210

Technical specifications	SW 30	SW 50	SW 100
Load-carrying capacity	3 t	5 t	10 t
Stroke	335 mm	335 mm	345 mm
Length	296 mm	189 mm	250 mm
Width/depth	197 mm	335 mm	498 mm
height	730 mm	730 mm	800 mm
Weight	21.2 kg	28.5 kg	46.8 kg

- ▶ Stable design as per DIN 7355
- ▶ With self-arresting safety thrust roller crank



SW 30

– Hydraulic machine lift

- ▶ Stable, welded steel design for demanding applications
- ▶ For safe lifting of heavy loads
- ▶ Pump unit rotatable
- ▶ Removable pump lever
- Equipment HMH 5:**
 - ▶ 360° rotatable grab and/or base plate
- Equipment HMH 10:**
 - ▶ 360° rotatable grab and/or base plate
- Equipment HMH 25:**
 - ▶ Chassis

Model	HMH 5	HMH 10	HMH 25
Art. no.	6190050	6190100	6190250

Technical specifications	HMH 5	HMH 10	HMH 25
Load lifting capacity	5 t	10 t	25 t
Hand force at rated load	380 N	400 N	400 N
Stroke	205 mm	230 mm	215 mm
Underride height of lifting grab	25 mm	30 mm	58 mm
Underride height of lifting head	368 mm	420 mm	505 mm
Operating temperature range	-20 °C - +50 °C	-20 °C - +50 °C	-20 °C - +50 °C
Dimensions (L x W x H)	360 x 190 x 430 mm	380 x 220 x 510 mm	530 x 350 x 610 mm
Weight	25 kg	35 kg	109 kg



HMH 5

HMH 10

HMH 25