

TECHNICAL DATA SHEET

HO904 TREKKER VULCAN WOOD GRAIN USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS

(See Havwoods Quick Reference Guide to choosing the correct floor).



TREKKER VULCAN WOOD GRAIN

PRODUCT DETAILS

Product Reference	HO904
Width x Thickness	143 x 22mm
Board Type	Wood Grain
Pattern	1-Strip Plank
Length	3.2m
Composition	Wood Flour/Polymer



The mark of responsible forest

Maintenance Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors.

INSTALLATION METHODS

No			
Clips and screws are included (please ask a member of staff for details)			
No			
No			
Europe			

TECHN	$\Gamma \Lambda \Gamma$	CDI.	TEDIA
LECHIN	ICAL	CRI	IERIA

ILCIINICAL CRITERIA					
Characteristics	Requirements - EN 15534-4	Result			
Humidity	Declaration	1.10%			
Cupping	Declaration	0.05mm			
Density	Declaration	1435 Kg/m³			
Slip Resistance	≥ 36	60 PTV (Dry) 46 PTV (Wet)			
Impact Resistance	≤ 0.5mm	Max 0.10mm			
Flexural Properties	F ¹ Max 3300N (Mean) F ¹ Max 3000N (Individual) Deflection under load (mean) Deflection under load (individual)	4164N 3573N 1.7mm 2.0mm			
Swelling and Water Absorption	Absorption (Mean) ≤ 4% (thickness) ≤ 0.8% (width) ≤ 0.4% (length)	2.00% 0.20% 0.01%			
	Absorption (Individual) ≤ 4% (thickness) ≤ 1.2% (width) ≤ 0.6% (length) Mean Absorption < 7% Individual Maximum < 9%	2.50% 0.30% 0.10% 1.40% 1.50%			
Boiling Test	≤ 7% (mean)	1.70%			
Composition	Declaration	40%/60% Woo 40%/60% Polyr 10% Others			
Vicat	Declaration	85.2°C			
HDT	Declaration	74°C			
Coef. Thermal expansion	≤ 50 x 10-6K	2.79 x 10-5mm/	/mm°C		
Resistance to artificial weathering	Declaration	ΔL < 5			
Mark	Declaration	EN15534-4 PVC	W 50 UC3		

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

INSTALL ATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.





