



TECHNICAL DATA SHEET

TREKKER ANTHRACITE FLUTED

HO912 TREKKER ANTHRACITE FLUTED USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS

(See Havwoods Quick Reference Guide to choosing the correct floor).



PRODUCT DETAILS

Product Reference	HO912
Width x Thickness	143 x 22mm
Board Type	Fluted Wood/Resin Composite
Pattern	1-Strip Plank
Length	3.2m
Composition	Wood Flour/Polymer
Maintenance	Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors.



INSTALLATION METHODS

Fully Bonded	No
Fixing	Clips and screws are included (please ask a member of staff for details)
Floated on underlay	No
Over Under Floor Heating	No
Origin:	Europe

TECHNICAL CRITERIA

Characteristics	Requirements - EN 15534-4	Result
Humidity	Declaration	1.00%
Cupping	Declaration	0.05mm
Density	Declaration	1455 Kg/m ³
Slip Resistance	≥ 36	60 PTV (Dry) 46 PTV (Wet)
Impact Resistance	≤ 0.5mm	Max 0.10mm
Flexural Properties	F ¹ Max 3300N (Mean) F ¹ Max 3000N (Individual) Deflection under load (mean) Deflection under load (individual)	5092N 4590N 0.4mm 0.5mm
Swelling and Water Absorption	Absorption (Mean) ≤ 4% (thickness) ≤ 0.8% (width) ≤ 0.4% (length) Absorption (Individual) ≤ 4% (thickness) ≤ 1.2% (width) ≤ 0.6% (length) Mean Absorption < 7% Individual Maximum - 7%	3.20% 0.30% 0.20% 4.20% 0.30% 0.30% 3.30% 3.60%
Boiling Test	≤ 7% (mean)	2.90%
Composition	Declaration	40%/60% Wood 40%/60% Polymer 10% Others
Vicat	Declaration	85.2°C
HDT	Declaration	74°C
Coef. Thermal expansion	≤ 50 x 10 ⁻⁶ K	2.79 x 10 ⁻⁵ mm/mm°C
Resistance to artificial weathering	Declaration	ΔL < 5
Mark	Declaration	EN15534-4 PVC W 50 UC3

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.



Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth LA5 9FD
T.+44(0)1524 737000 F.+44(0)1524 737001
info@havwoods.co.uk www.havwoods.co.uk