

TECHNICAL DATA SHEET

HO924 TREKKER VULCAN GROOVED USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS

(See Havwoods Quick Reference Guide to choosing the correct floor).



TREKKER VULCAN GROOVED

PRODUC	T DETA	
110000		

Product Reference	HO924		
Width x Thickness	143 x 22mm		
Board Type	Grooved	FSC	
Pattern	1-Strip Plank	www.fsc.org FSC* C009500	
Length 3200mm		The mark of	
Composition	Wood/Polymer Composite	responsible forestry	
Maintenance	Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors.		

INSTALLATION METHODS

Fully Bonded		No		
Fixing		Clips and screws are included (please ask a member of staff for details)		
Origin:		Europe		

TECHNICAL CRITERIA

TECHNICAL CRITERIA						
Characteristics	Requirements - EN 15534-4	Result				
Humidity	Declaration	1.10%				
Cupping	Declaration	0.08mm				
Density	Declaration	1435 Kg/m ³				
Slip Resistance	≥ 36	65 PTV (Dry) 55 PTV (Wet)				
Impact Resistance	≤ 0.5mm	Max 0.10mm				
Flexural Properties	F ¹ Max 3300N (Mean) F ¹ Max 3000N (Mean) Deflection under load (mean) Deflection under load (individual)	4164N 3573N 1.7mm 2.0mm				
Swelling and Water Absorption	Absorption (Mean)≤ 4% (thickness)≤ 0.8% (width)≤ 0.4% (length)	2.00% 0.20% 0.01%				
	Absorption (Individual) ≤ 4% (thickness) ≤ 1.2% (width) ≤ 0.6% (length) Mean Absorption < 7% Individual Maximum < 9%	2.50% 0.30% 0.10% 1.40% 1.50%				
Boiling Test	≤ 7% (mean)	1.70%				
Composition	Declaration	40%/60% Wood 40%/60% Polymer 10% Others				
Vicat	Declaration	85.2°C				
HDT	Declaration	74°C				
Coef. Thermal expansion	≤ 50 x 10-6K	2.79 x 10-5mm/m	۱m°C			
Resistance to artificial weathering	Declaration	ΔL < 5	ΔL < 5			
Mark	Declaration	EN15534-4 PVC \	N 50 UC3			

* Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Havwoods Limited. Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Havwoods Limited, Carnforth Business Park, Oakwood Way, Carnforth LA5 9FD T.+44(0)1524 737000 F.+44(0)1524 737001 info@havwoods.co.uk www.havwoods.co.uk

