

TECHNICAL DATA SHEET

HO926 TREKKER EARTH GROOVED USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS

(See Havwoods Quick Reference Guide to choosing the correct floor).



TREKKER EARTH GROOVED

PRODUCT DETAILS

Product Reference	HO926
Width x Thickness	143 x 22mm
Board Type	Grooved
Pattern	1-Strip Plank
Length	3200mm
Composition	Wood/Polymer Composite



The mark of responsible forest

Maintenance Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors.

INSTALLATION METHODS

Fully Bonded	No	
Fixing	Clips and screws are included (please ask a member of staff for details)	
Origin:	Europe	

TECHNICAL CRITERIA			
Characteristics	Requirements - EN 15534-4	Result	
Humidity	Declaration	1.10%	
Cupping	Declaration	0.08mm	
Density	Declaration	1435 Kg/m³	
Slip Resistance	≥ 36	65 PTV (Dry) 55 PTV (Wet)	
Impact Resistance	≤ 0.5mm	Max 0.10mm	
Flexural Properties	F ¹ Max 3300N (Mean) F ¹ Max 3000N (Mean) Deflection under load (Mean) Deflection under load (Individual)	4164N 3573N 1.7mm 2.0mm	
Swelling and Water Absorption	Absorption (Mean) ≤ 4% (thickness) ≤ 0.8% (width) ≤ 0.4% (length)	2.00% 0.20% 0.01%	
	Absorption (Individual) ≤ 4% (thickness) ≤ 1.2% (width) ≤ 0.6% (length) Mean Absorption < 7% Individual Maximum < 9%	2.50% 0.30% 0.10% 1.40% 1.50%	
Boiling Test	≤ 7% (mean)	1.70%	
Composition	Declaration	40%/60% Wood 40%/60% Polymer 10% Others	
Vicat	Declaration	85.2°C	
HDT	Declaration	74°C	
Coef. Thermal expansion	≤ 50 x 10-6K	2.79 x 10-5mm/mm°C	
Resistance to artificial weathering	Declaration	ΔL < 5	
Mark	Declaration	EN15534-4 PVC W 50 UC3	

^{*} Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.

INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.





