

## **TECHNICAL DATA SHEET**

# HO966 TREKKER ANTHRACITE FASCIA - 2-SIDED USAGE: COMMERCIAL AND RESIDENTIAL APPLICATIONS



## TREKKER ANTHRACITE FASCIA

### PRODUCT DETAILS

Product Reference	HO966		
Width x Thickness	100 x 11mm		
Board Type	2-Sided Flexitrim		
Pattern	1-Strip Plank		
Length	1500mm		
Composition	Wood/Polymer Composite		



The mark of responsible forest

Maintenance Comprehensive cleaning and maintenance instructions and materials are available from Havwoods Ltd. for all floors.


#### **INSTALLATION METHODS**

Fully Bonded	No	No			
Fixing	Clips and screws are included (please ask a member of staff for details)				
Origin:	Europe				

TECHNICAL CRITERIA				
Characteristics	Requirements - EN 15534-4	Result		
Humidity	Declaration	0.31%		
Cupping	Declaration	0.06mm		
Density	Declaration	1459 Kg/m <sup>3</sup>		
Impact Resistance	≤ 0.5mm	Max 0.12mm		
Flexural Properties	F <sup>1</sup> Max 3300N (Mean) F <sup>1</sup> Max 3000N (Mean) Deflection under load (Mean) Deflection under load (Individual)	1274N 1228N 1.6mm 1.7mm		
Swelling and Water Absorption	Absorption (Mean) ≤ 4% (thickness) ≤ 0.8% (width) ≤ 0.4% (length)	3.00% 0.60% 0.20%		
	Absorption (Individual)  ≤ 4% (thickness)  ≤ 1.2% (width)  ≤ 0.6% (length)  Mean Absorption < 7%  Individual Absorption < 9%	3.60% 0.70% 0.30% 3.90% 4.20%		
Boiling Test	≤ 7% (mean)	3.70%		
Composition	Declaration	40%/60% Wood 40%/60% Polymer 10% Others		
Vicat	Declaration	85.2°C		
HDT	Declaration	74°C		
Coef. Thermal expansion	≤ 50 x 10-6K	2.79 x 10-5mr	m/mm°C	
Resistance to artificial weathering	Declaration	ΔL < 5		
Mark	Declaration	EN15534-4 P	VC W 50 UC3	

#### INSTALLATION AND WARRANTY

All Havwoods floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Havwoods warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.







<sup>\*</sup> Subject to compatible subfloor and correct installation (see Installation Guidelines) including sensors.