



1. Shock Mount (Front) - 8Nm  
LSSMF-1.0



2. Shock Mount (Rear) - 8Nm  
LSSMR-1.0



3. Rocker (Upper) - 8-10Nm  
LSRU-1.2



4. Rocker (Lower) - 10-12Nm  
LSRL-1.2



5. Main Pivot - 10-12 Nm  
LSMP-1.2



6. Chainstay Pivot (2x) - 5-7Nm  
LSCSP-1.2



Frame:	La Sal Peak
Year:	2019
Wheel Size:	29"/27.5+
Material:	Carbon
Front Travel:	160-170mm
Rear Travel:	150mm
Tire Compatibility:	29x2.6, 27.5x2.8
Rear Dropout:	148mm (boost)
Rear Axle:	174x12x1.75mm
Rear Brake Mount:	180 Post Mount
Bottom Bracket:	73mm English Thread
Seatpost Diameter:	31.6mm
Clamp Diameter:	34.9mm
Dropper Routing:	Internal
Headset Standard:	ZS44/ZS56
Shock Length:	210mm
Shock Stroke:	55mm
Front Hardware:	M8x25
Rear Hardware:	M8x25
Seatstay Bearings:	4x 6900 (10x22x6mm)
Rocker Bearings:	2x 6901 (12x24x6mm)
Main Bearings:	2x 6902 (15x28x7mm)
Max Chaining:	34 round
Bashguard Mount:	ISCG-05
Derailleur Hanger #:	14
Chaining Offset:	3 mm