



PLATFORM SIZE	A	B	C	D	E
36X48	36.25	48	51.18	7.13	31.81
36X54	36.25	54	51.18	7.13	31.81
36X60	36.25	60	51.18	13.13	31.81
42X54	42.25	54	57.18	7.13	34.81
42X60	42.25	60	57.18	13.13	34.81

Specifications
 Model: VP19
 Rated Load: 750 lbs
 Drive: Dual winding cable drums / 24 VDC
 500 watt motor w/brake
 Supply Power: 120 VAC 15A
 Operating Power: 24 VDC (DUAL 12V 10AH BATTERIES)
 Control Power: 5 VDC
 Platform: 36" x 48" (36" x 54") (36" x 60")
 (42" x 54") (42" x 60")
 Lift Height: 1" - 144"
 Speed: 15-18 fpm
 Controls: Constant pressure paddle switch
 Safety Standards: ASME A18.1, Section 2
 CSA B44.1/ASME A17.5
 Safety Features: Safety pan, final limit, slack cable brake,
 emergency stop w/alarm

**DESIGNED TO COMPLY
 WITH ANSI A18.1 PART 2
 WHEN PROPERLY INSTALLED**

MODEL	X	Y
PLO-048	48	93.06
PLO-072	72	117.06
PLO-096	96	141.06
PLO-0120	120	165.06
PLO-0144	144	189.06

SHCA
STAYING HOME CORPORATION

Staying Home Corporation
 2501 Anaconda Rd
 Harrisonville, MO 64701
 816-380-2427
 www.stayinghome.com

TITLE: PLATFORM LIFT - OPEN
 FREE STANDING

SIZE B	DWG. NO. TYP-PLO-FS	REV 05/09 2019
-----------	------------------------	----------------------

SCALE: WEIGHT: SHEET 1 OF 1