

FY-1600SE



64" HEAT-ASSISTED LAMINATOR

The Fayon FY-1600SE is a high-performance laminator for demanding applications. Class-leading features provide ease-of-use and quality results. Laminates, mounts graphics and applies application tape and adhesive. Compatible with all types of cold lamination film.

WHY FY-1600SE?

- Robust construction for heavy use
- Fast load/unload, 64" aluminum shafts
- Heated upper-roller prevents "silvering"
- Pneumatically controlled roller pressure
- Control-panels, front and rear
- High-speeds for long runs
- Versatile: Laminates, encapsulates, mounts & masks

SUITABLE FOR:

- Flexible printed materials
- Pop-up and roll-up banners
- Mounting to rigid materials
- Applying application tape
- Outdoor signage
- Vehicle wraps
- Floor graphics
- Backlit displays



Heavy-duty frame



5 easy-load feed/rewind shafts



Edge-trimming & slitter system



Tension-control on all shafts




Convenient front & rear controls




Material-sensing & auto-stop




Easy webbing for a variety of laminating uses



Liner film laminating



Linerless film laminating



Laminating with cutting

Specifications:

Max laminating width:	63.75" (1620mm)
Max laminating thickness:	1.37" (35mm)
Max speed: 1	49.2ft/min (5m/min)
Max temp:	256 deg F (125 deg C)
Heating:	Infrared
Preheating time:	10-15min
Roller actuation:	Air Cylinder
Roller material:	Silicone
Voltage:	110V
Power consumption:	0.8~2.5kw/h
Air Compressor Included?:	Yes
Air Requirements (if not using supplied compressor):	58psi (0.4MPa)
Assembled Dimensions (W x D x H):	80" x 27" x 52"
Assembled Weight:	550lbs
Packed dimensions (W x D x H):	87" x 33" x 33" (wooden crate)
Packed weight:	620lbs



Plotter Mechanix 7800 N 55th Ave, #102-225 Glendale, AZ 85301 602-606-8845 sales@plottermechanix.com