HP DesignJet T2600 Multifunction Printer series



ENGINEERED FOR COLLABORATION—Turn your workgroups into highly efficient teams



SEAMLESS EXPERIENCE—Designed for all

- Radically simple experience with a 15.6-inch interface and the easy PDF printing with HP
- Engage in a collaborative workstyle with teams by quickly accessing shared folders to print and
- Empower your workforce. Easily print and share jobs from the cloud with your mobile device and HP Smart app
- Fits in your workplace as the most compact 36 inch All in One and quietest operation, with up to 87% less noise.2

UNLEASH PERFORMANCE—To turn design into delivery

- Showcase design versatility from precise line drafts to boldly colored 3D renders, with HP Bright Office Inks.
- Provide the highest accuracy and display the finest details with the unique Adobe PDF Print
- Meet deadlines with speeds up to 180 D/hr, the industries only integrated stacker 2, and dual rolls.6
- · Easily digitize your projects with automated scanning, user-centric quicksets, and postediting capabilities.

SECURE—World's most secure large-format printer1

- Best of class network protection with features like HP Secure Boot and whitelisting
- Control who accesses the printer and its confidential documents with secure user authentication features
- Keep your fleet secure with HP JetAdvantage Security Manager.

For more information, please visit http://www.hp.com/go/designjett2600

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019.

Based on comparable large-format inkjet printers under \$12,000 (USD) as of December, 2018. IDC figures show that Canon, Epson, and HP combine for 98% share of this printing category worldwide as of Q3, 2018. Most compact footprint calculated using all devices in "Operation mode" with an Open Basket and the arm of the Screen (front panel) spread out to enable user interaction and the scanner lifted on the Canon TX 3000 T36 MFP and the Epson SC-T5200 MFP to enable top media loading. Most quiet according to internal HP testing of sound pressure level during operating mode (plain paper, line drawing, Normal mode) compared to published specification of competitive printers. Percentage calculations of noise based on lineal units vs. Canon TX-3000 published spec of 51dB(A). Fastest print speed based on sustained printing speeds. Only automatic print stacking based on unicity of the integrated stacker versus competitive printers only offering basket or bin with stacking position ³ Using Lightweight Directory Access Protocol (LDAP).

⁴ Compared to Canon Direct Print & Share and based on "One Click Print." Once image is selected, one-click printing when printing the entire file without any modifications to the print settings. Applicable to PDF, JPEG, TIFF,

Requires purchase of the HP DesignJet T2600 PostScript® models or optional HP DesignJet PostScript/PDF Upgrade Kit. Highest accuracy and finest details compared to printers without the embedded Adobe technology excluding RIP users, and based on internal HP testing with PDF files containing special forus, PANTONE® colors, smooth shading, overprint, and transparencies that can only be reproduced using the Adobe PDF Print Engine. The Adobe PDF Print Engine (APPE) is Adobe's high speed, high fidelity print platform. To learn more, visit http://www.adobe.com/products/pdfprintengine.

Dual rolls included with HP DesignJet T2600dr multifunction printers only.

Pint resolution Up to 2400 x 1200 optimized dipi Technology HPT Thermal Insiget RoBE 3 x 32 x 3 x mm (0.12 x 0.12 x 0.12 x 0.12 x 0.12 m) RoBE 3 x 32 x 3 x mm (0.12 x 0.12 x 0.12 x 0.12 x 0.12 m) Next yees Debased (W. Y. FK. Gipplemen-based (mK) Pinthads Lundersal printhead Scan: Up 10 3 in/sec (7.62 cm/sec) color at 200 dpl) Malifunction capabilities Scan: Up 10 3 in/sec (7.62 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp: Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp. Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp. Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp. Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp. Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp. Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Corp. Up to 6 in/sec (15.44 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/se	Print speed	180 A1/D hr, A1/D in 19.3 sec on plain media
Margins Soil 3.1 x 3.1 x 3.1 xm (N.12.x 0.12 x		
Sheet 3 x 22 x 3 x 3 x m (0.12 x 0.03 x 0.12 x 0.012 m) Deve based (CM, Y, EK, Gi pigment-based (mK) Printheads 1 universal printhead 1 universal printhead 1 universal printhead 0.0008 in (0.02 mm) (PDF addressable @ 1200 dpi) Multifunction capabilities Scan: Up to 3 in/sec (7.62 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi copy: Up to 600 dpi Multifunction capabilities Scan: Up to 3 in/sec (7.62 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi copy: Up to 600 dpi Maximum scans width .PEG-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); PDF-36 x	Technology	HP Thermal Inkjet
Init types Dye based (C, M, Y, pK, Gi; pigment based (mN) Printhesids 1 universal printhesid 1 universal printhesid 1 universal printhesid Double (D, 2008) in (D, 20 mm) (PDF addressable @ 1200 dpl) Multifunction capabilities Scan: Up to 3 in/sec (7,62 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy: Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Constant (15.24 cm/sec) cm/sec (15.24 cm/sec) cm/sec (15.24 cm/sec) grayscale at 200 dpl Constant (15.24 cm/sec) cm/sec (15.24 cm/sec) cm/sec (15.24 cm/sec) cm/sec (15.24 cm/sec) grayscale at 200 dpl Constant (15.24 cm/sec) cm/sec (15.24 cm	Margins	
Printheads 1 universal printhead	Ind. to on an	
Line accuracy		
Minimum line width 0.0008 in (0.02 mm) (PDF addressable el 1200 dpl) Multifunction capabilities Scan: Up to 3 in/sec (7.62 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Copy; Up to 6 in/sec (15.24 cm/sec) color at 200 dpl, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpl Maximum scan size Maximum scan width JPEG-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 15,000 mm)		
Multifunction capabilities Sam: Up to 3 in/sec (7.62 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi Scan resolution Up to 60 dpi Maximum scan size Maximum scan width JPEG-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm) Thickness 0.03 in (0.8 mm) Scan destinations USB, shared network foldec printer HDD, email Media Handling Sheet feed, front-loading roll feed, roll switching , integrated 100 page output stacker, media bin, automatic horizontal cutter Scanness and the state of the state		
Scan: Up to 3 in/sec (7.62 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi Copy. Up to 6 in/sec (15.44 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi Copy. Up to 6 in/sec (15.44 cm/sec) color at 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale at 200 dpi Maximum scan size Maximum scan width JPEG-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 9000 mm); PDF-36 x 315 in (914 x		olooo iii (oloo iiiii) (i oli dadiessaale gi 1200 api)
Meximum scan size Meximum size Meximum size Meximum size Meximum s	-idation capabilities	
(914 x 8000 mm) 7 Thickness 0.03 in (0.8 mm) Scan format JPEG, FIFF and multipage TIFF, PDF and multipage PDF Scan destinations USB, shared network folder, printer HDD, email Media Handling Sheet feed, front-loading roll feed, roll switching , integrated 100 page output stacker, media bin, automatic horizontal cutter Scanner-straight-through scan paper path for sheet and cardboard originals Sheet size 8.3 x 11 to 36 x 48 in (210 x 279 to 914 x 1219 mm) Roll size 11 to 36 in (279 to 914 mm) holds up to 300ft Standard sheet A, A3, A3, A1, A0 (A, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications United drawings: Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing) Hard disk 500 GB self-encypting Connectivity Interfaces Gligabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, Boott/PDHCP (IPv4 only), DHCPv4, Tri (IPv4 only), SNMP (V1, V2c, V3), Apple Bonijour Compatible, W5 Discovery, Embedded Web Server (HTTP; HTTPS; BPR4 EAPHTS), DPS TeaPHTS, D	Scan resolution	
Scan format JPEG, TIFF and multipage TIFF, PDF and multipage PDF Scan destinations USB, shared network folder, printer HDD, email Media Handling Sheet feed, front-loading roll feed, roll switching , integrated 100 page output stacker, media bin, automatic horizontal cutter Scanner straight-through scan paper path for sheet and cardboard originals Sheet size 3.3 x 11 to 36 x 48 in (210 x 279 to 914 x 1219 mm) Roll size 11 to 36 in (279 to 914 mm) holds up to 300ft Standard sheets Al, A3, A2, A1, A0 (N, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings, Mapps Orthophotos; Presentations; Renderings Memory 128 GB (Rie processing) Hard disk 500 GB self-encypting Connectivity Interfaces Gigabit Ethernet (1008se-T), supporting the following standards: TCPIP BootP/DHCP (IPv4 only), DHCPv6, Till Presentations; Persentations; Renderings Hard disk 500 GB self-encypting Connectivity Interfaces Gigabit Ethernet (1008se-T), supporting the following standards: TCPIP BootP/DHCP (IPv4 only), DHCPv6, Till Presentations; Persentations; Persent	Maximum scan size	Maximum scan width JPEG-36 x 315 in (914 x 8000 mm); TIFF-24 x 590.5 in (610 x 15,000 mm); PDF-36 x 315 in (914 x 8000 mm) 7
Scan destinations USB, shared network folder, printer HDD, email	Thickness	0.03 in (0.8 mm)
Sheet feed, front-loading roll feed, roll switching , integrated 100 page output stacker, media bin, automatic horizontal cutter Scanner, straight-through scan paper path for sheet and cardboard originals	Scan format	JPEG, TIFF and multipage TIFF, PDF and multipage PDF
Sheet feed, front-loading roll feed, roll switching , integrated 100 page output stacker, media bin, automatic horizontal cutter Scanner's straight through scan paper path for sheet and cardboard originals Sheet size 8.3 x 11 to 36 x 48 in (210 x 279 to 914 x 1219 mm) Sandard sheets An, A3, A2, A1, A0 (A, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing) Hard disk 500 GB self-encrypting Connectivity Interfaces Gligabit Ethernet (1000Base-T), supporting the following standards TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, Tri (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS; MTP (email), Raw IP printing (9100), IPD, IPW, Sprint, TNTL, Sp021.X authentication (LEA) Print languages (standard) Print Languages (standard) Print Languages (standard) Print Languages (standard) Print Languages (optional) Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, Service for Android, Apple AlPrint driver for MiscOS and for 10, S, HP Print for Chome OS, HP Click, HP Smart Ag and Android Drivers PostScript Printer: Assets, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPs, JR Herbert of Control	Scan destinations	USB, shared network folder, printer HDD, email
horizontal cutter Scanner straight-through scan paper path for sheet and cardboard originals Sheet size 8.3 x 11 to 36 x 48 in (210 x 279 to 914 x 1219 mm) Boll size 11 to 36 in (279 to 914 mm) holds up to 300ft Standard sheets A4, A3, A2, A1, A0, A0, A, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings: Maps, Orthophotos; Presentations; Renderings Memory 128.68 (file processing) Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (10008ase-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, Tri (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS) SMTP (email), Raw IP printing (9100), IPO, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (ILEA) PRINT Languages (satindard) PostScript Printer. Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIPF, JPEG, CALS G4 Print Languages (potional) Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, H Service for Android, Apple AirPrint driver for MacOS and for IOS, HP Print for Chrome OS, HP Click, HP Smart A; and Android Drivers PostScript Printer. Baster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Bost, Withielisting, TPM, Role Based Access Control, LDAP and Kethers authentication, SNMPv3, HT Secure HPP. IPBec/Firewall, Certificates management, 80.11 X; 15.10.11 /1.2 HP Wios betadmin compatible, HP Jerkd-Andraige-Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security loggling Dimensions (w x d x h) Printer Storage temperature 4.1 to 95°F (S to 35°C) Acoustics Sound power 4.2 dB(A) (operating); 3.2 dB(A) (idle); < 17 dB(A) (sleep) Operating humidity 20 to 80°S RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics	Media	
Sheet size 8.3 x 11 to 36 x 48 in (210 x 279 to 914 x 1219 mm) Roll size 11 to 36 in (279 to 914 mm) holds up to 300ft Standard sheets A4, A3, A2, A1, A0 (A, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 56 glife processing) Hard disk 500 68 self-encrypting Connectivity Interfaces Gigabit Ethernet (10008ase-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, Tri (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP; HTTPS) SMP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEA) PERA EAP-TLS, DFS Print languages (standard) PostScript p1, 3A dobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, IPP driver for Windows, H Service for Android, Apple AirPrint driver for MacCoS and for IOS, IHP Print for Chrome OS, IHP Click, IHP Smart A; and Android Drivers PostScript Printer Raster, PostScript and EDF drivers for Windows, AirPrint for macOS Security features HP-Secure Boot, Wisterials, Certificates management, 802.1X, TLS 1.0/1.1/1.2, IHP Web Jetadmin compatible, IHP HD, encrypted PIN printing, Syslog security logging Dimensions (w.x.d.x.h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer 5 Single-roil: 229 ib (104 kg), dual-roil: 240 ib (109 kg) Shipping 5 Single-roil: 239 ib (104 kg), dual-roil: 240 ib (109 kg) What's in the box IHP Designale T2600 Multifunition Printer printer stand and media bin, 15.6" touchscreen, spindle(s), printhead introductory in Karridges, user guide, power cords HP Software and Solutions IHP Cick, HP mobile, eprint and (OSAndroid support plus the HP Smart app for mobile, IHP Web Jetadmin, HP JetAdvantage Security Managet IHP SmartTracker (optional) Finiter 5 to 13 to 1311°F (-25 to 55°C)	Handling	horizontal cutter
Roll size	Sheet size	
Standard sheets A4, A3, A2, A1, A0 (A, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 G8 (file processing) Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, Ti (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP; HTTP5; SMP (Pemall), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEA) PEAR_EAP-TLS, DP5 Print languages (standard) PostScript 3, Adobe POST-Cript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, Asir Print flampaths Service for Android, Apple AirPrint driver for MacOS and for IOS, HP Print for Chrome OS, HP Click, HP Smart Ag and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Book, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT JEDA, HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping Single-roll: 209 ib (104 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 200 ib (136 kg), dual-roll:		
Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing) Hard disk 500 GB self-encrypting Connectivity Interfaces Glapbit Ethernet (1008ase-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TI, (IPv4 only), SNMP (1v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP; HTTPS) SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEA PEAP TLS), DE? Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared foldes email printing, HP driver for Windows, H Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart Agand Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IPSec/Firewall, Certificates management, 802.1X, TLS 1.0/1.17, L.P, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dirnersions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping Single-roll: 300 ib (136 kg), dual-roll: 240 ib (109 kg) Shipping Single-roll: 300 ib (136 kg), dual-roll: 306 ib (139 kg) What's in the box HP Designuler: 12600 Multifunition Printee, printer stand and media bin, 15.6° touchscreen, spindle(s), printhead introductory ink cartridges, user guide, power cords HP Designuler: 12600 Multifunition Printee, printer stand and media bin, 15.6° touchscreen, spindle(s), printhead introductory ink cartridges, user guide, powe		
Thickness Up to 0.5 mm (19.7 mil) Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing) Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, Till (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP (email), Raw IP printing (1900), LPD, IPP, W6 printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP (email), Raw IP printing (1900), LPD, IPP, W6 printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP (email), Raw IP printing (1900), LPD, IPP, W6 printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP (email), Raw IP printing (1900), LPD, IPP, W6 printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; SMTP, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; DFC, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; DFC, Email Printing, V5 Discovery, Embedded Web Server (HTTP, HTTP5; DFC, Embedded Web Server (HTTP, HTTP5; DFC, Embedded Web Server, HTTP5		
Applications Line drawings; Maps; Orthophotos; Presentations; Renderings Memory 128 GB (file processing) Hard disk 500 GB self-encrypting Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TI (IPv4 only), SMMP (v1, v2c, v3), Apple Bonjour Compatible, W5 Discovery, Embedded Web Server (HTTP; HTTPS) SMTP (email), Raw IP printing (9100), LPD, IPP, W5 print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAI PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe POstScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, And Androdid Drives PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for Chrome OS, HP Click, HP Smart Ap and Androdid Drives PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-HPI, Psec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syolog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm)		-
Connectivity	Applications	
Connectivity		
Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TI (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS) SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAI PEAP, EAP-TLS), DES Print languages (standard) PostScript 3, Adobe POStScript 3, Adobe PDF 1.7 Printlanguages (optional) Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, H Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart Ap and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Letadmin compatible, Put Advantage Securely Manager compatible, Secure Disk erase (Dob 5220.22-M), Secure File erase, self-encypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 56.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's In the box HP Design-ter T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead intoductory in k cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature 42 dB(A) (operating); ≤ 4.9 B(A) (idle); < 17 dB(A) (Hard disk	
(IP'v4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP HTTPS) SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAI PEAP, EAP-TLS), DFS Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Print languages (optional) Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, H Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart Ag and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IP-sec/Firewall, Certificates management, 802.1X, TLS 1.0/11.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP Designet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Acoustics Sound power 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power 5.9 B(A) (operating); < 4.9 B(A) (idle); < 10 U (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Connectivity	
Print languages (optional) Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, H Service for Android, Apple AirPrint driver for MacOS and for IOS, HP Print for Chrome OS, HP Click, HP Smart Ag and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IPsec/Firewall, Certificates management, 80.2.1 X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP Jetadvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power ≤ 5.9 B(A) (operating); ≤ 4.9 B(A) (idle); < 17 dB(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Interfaces	Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IP SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-TLS), DFS
Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, H Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart Ag and Android Drivers PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Ervironmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature 41 to 95°F (5 to 35°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power \$\leq 5.9 B(A) (operating); \$\leq 4.9 B(A) (idle); \leq 1.7 dB(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Print languages (standard)	PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4
Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart Ap and Android PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature 41 to 95°F (5 to 35°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power \$\leq 5.9 B(A) (operating); \(\frac{1}{2} \) 4.9 B(A) (idle); \(\frac{1}{2} \) 5.8 (A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Print languages (optional)	Adobe PostScript 3, Adobe PDF 1.7
Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HT Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating temperature 41 to 95°F (5 to 35°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power < 5.9 B(A) (operating); < 3.6 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Printing paths	Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP P Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App f and Android
Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdwantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypt HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power \$ 5.9 B(A) (operating); < 4.9 B(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Drivers	PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS
Printer 55 x 30 x 49 in (1390 x 760 x 1240 mm) Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating temperature 41 to 95°F (5 to 35°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power ≤ 5.9 B(A) (operating); 32 dB(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Security features	JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting
Shipping 58.3 x 30.3 x 32 in (1480 x 770 x 810 mm) Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power < 5.9 B(A) (operating); < 4.9 B(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Dimensions (w x d x h)	
Weight Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating temperature 41 to 95°F (5 to 35°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power ≤ 5.9 B(A) (operating); 34 B(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Printer	55 x 30 x 49 in (1390 x 760 x 1240 mm)
Printer Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg) Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s), printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power \$\leq 5.9 B(A) (operating); < 3.6 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Shipping	58.3 x 30.3 x 32 in (1480 x 770 x 810 mm)
Shipping Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg) What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power < 5.9 B(A) (operating); 3.9 B(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Weight	
What's in the box HP DesignJet T2600 Multifuntion Printer, printer stand and media bin, 15.6" touchscreen, spindle(s) , printhead introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power \$\leq 5.9 B(A) (operating); < 4.9 B(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Printer	Single-roll: 229 lb (104 kg), dual-roll: 240 lb (109 kg)
introductory ink cartridges, user guide, power cords HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP Jetadvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power < 5.9 B(A) (operating); 32 dB(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Shipping	Single-roll: 300 lb (136 kg), dual-roll: 306 lb (139 kg)
JetAdvantage Security Manager, HP SmartTracker (optional) Environmental ranges Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power ≤ 5.9 B(A) (operating); ≤ 4.9 B(A) (idle); < 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	What's in the box	$HP. Design Jet T2600 \ Multifuntion \ Printer, printer \ stand \ and \ media \ bin, 15.6" \ touch screen, \ spindle(s) \ , \ printheads, introductory ink cartridges, user guide, power cords$
Operating temperature 41 to 95°F (5 to 35°C) Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics -10 to 131°F (-25 to 55°C) Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep)	HP Software and solutions	
Operating humidity 20 to 80% RH Storage temperature -13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep)	Environmental ranges	
-13 to 131°F (-25 to 55°C) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep) Sound power ≤ 5.9 B(A) (operating); ≤ 4.9 B(A) (idle); ≤ 3.5 B(A) (sleep) Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Operating temperature	41 to 95°F (5 to 35°C)
Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep)	Operating humidity	20 to 80% RH
Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep)	Storage temperature	-13 to 131°F (-25 to 55°C)
Sound power ≤ 5.9 B(A) (operating); ≤ 4.9 B(A) (idle); ≤ 3.5 B(A) (sleep) Power 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Acoustics	
Power Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Sound pressure	42 dB(A) (operating); 32 dB(A) (idle); < 17 dB(A) (sleep)
Consumption 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)	Sound power	\leq 5.9 B(A) (operating); \leq 4.9 B(A) (idle); \leq 3.5 B(A) (sleep)
	Power	
	Consumption	120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)
nequirements input voitage (auto ranging) 100-240 v (±10%), 50/60 fiz (±3 HZ), Z A Max	Requirements	Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max

PLOTTER MECHANIX SALES-SERVICE

USA and Canada (CSA certified)

ENERGY STAR, ErP, WEEE, REACH, EPEAT

One-year limited hardware warranty



Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES)









Ordering information

Prod	uc
------	----

Accession	
3XB78A	HP DesignJet T2600 36-in PostScript Multifunction Printer
3EK15B	HP DesignJet T2600dr 36-in PostScript Multifunction Printer
3EK15A	HP DesignJet T2600dr 36-in PostScript Multifunction Printer

HP SmartTracker USB for DesignJet HP SmartTracker for DesignJet HP DesignJet 3-in Core Adapter HP DesignJet 36-in Spindle HP USB 3.0 to Gigabit LAN Adapter 5NB95A 5NB95AAE CN538A L4R66A N7P47AA

Original HP printing supplies

B3P06A	HP 727 DesignJet Printhead	
P2V62A	HP 730 130-ml Cyan DesignJet Ink Cartridge	
P2V63A	HP 730 130-ml Magenta DesignJet Ink Cartridge	
P2V64A	HP 730 130-ml Yellow DesignJet Ink Cartridge	
P2V65A	HP 730 130-ml Matte Black DesignJet Ink Cartridge	
P2V66A	HP 730 130-ml Gray DesignJet Ink Cartridge	
P2V67A	HP 730 130-ml Photo Black DesignJet Ink Cartridge	
P2V68A	HP 730 300-ml Cyan Design et Ink Cartridge	
P2V69A	HP 730 300-ml Magenta DesignJet Ink Cartridge	
P2V70A	HP 730 300-ml Yellow DesignJet Ink Cartridge	
P2V71A	HP 730 300-ml Matte Black DesignJet Ink Cartridge	
P2V72A	HP 730 300-ml Gray DesignJet Ink Cartridge	
P2V73A	HP 730 300-ml Photo Black DesignJet Ink Cartridge	

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

Original HP large format printing materials

C6810A HP Bright White Inkjet Paper (FSC® certified)(recyclable)⁵ 36 in x 300 ft (914 mm x 91.4 m)

C6980A HP Coated Paper (PEFC™ certified) (recyclable)⁵ 36 in x 300 ft (914 mm x

L5C80A HP Universal Heavyweight Coated Paper, 3-in Core (FSC® certified) (recyclable) 36 in x 300 ft (914 mm x 91.4 m) **D9R28A** HP Everyday Matte Polypropylene, 3-in Core 36 in x 200 ft (914 mm x 61

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

- (UB9P6E (1-roll)/UB8U4E (2-roll) HP 3 year NBD Onsite HW Support with DMR
	UB9P7E (1-roll)/UB8U5E (2-roll) HP 4 year NBD Onsite HW Support with DMR
	UB9P8E (1-roll)/UB8U6E (2-roll) HP 5 year NBD Onsite HW Support with DMR
	UB9P9PE (1-roll)/UB8U7PE (2-roll) HP 1 year Post Warranty NBD Onsite HW
	Support with DMR

U1XV4E HP Preventive Maintenance Service
H4518E HP Installation Service with Network Setup

HP DesignJet Support Services offer installation, maintenance, and extended support services (e.g. 2,3, 4 and 5 years). For more information, please visit hp.com/go/cpc

or iOS **ECO highlights**

- Save paper with automatic print settings and image nesting ENERGY STAR® certified and EPEAT® registered Free, convenient HP ink cartridge recycling FSC®.certified papers®, recyclable HP media; some HP media eligible for takeback program®

Please recycle large-format printing hardware and printing supplies. Find out how at our website hp.com/ecosolutions

- ¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the
- U.S. Environmental Protection Agency.

 ² EPEAT® registered where applicable. EPEAT registration varies by country. See
- ² EPEAT* registered where applicable. EPEAT registration varies by country. See http://www.pepat.net for registration status by country.
 ³ Program availability varies. Please check http://www.hp.com/recycle for details.
 ⁴ BMG trademark license code FSC*-C115319see http://www.fsc.org. HP trademark license code FSC*-C017543, see http://www.fsc.org. Not all FSC*-certified products are available in all regions. For information about HP large format printing materials, please wisit http://www.HPLFMedia.com.
 Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

Original HP inks

Based on 8 GB RAM.

BMG trademark license code FSC*-C115319, see http://www.fsc.org. HP trademark license code FSC*-C115319, see http://www.fsc.org. BMG trademark license code FSC*-C017543, see http://www.fsc.org. BMG trademark license code PEFC**/29-31-261, see http://www.pefc.org. HP trademark license code PEFC**/29-31-298, see http://www.pefc.org. Not all FSC*- or PEFC**-certified products are available integries.

available inall regions.

avariable Inali regions.

⁵ Can be recycled through commonly available recycling programs.

⁶ Applicable for dual-roll printers only.

⁷ Applicable for PostScript printers only.

⁸ Single-roll printers come with one spindle, dual-roll printers come with two spindles.



Safety

Warranty

Electromagnetic

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.
² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0E HP Matte Film in Best or Normal mode with