



Product Specification



POLYESTER



38°C



sfwt.eu/spe



Ordering Details

Product Code	Micron (μ)	Standard Diameter Lengths (")	Large Diameter Lengths (")
SPE	0.5, 1, 5, 10, 20, 30, 50	4", 9¾", 20", 30, 40	9¾"BB, 20BB
<div style="display: flex; align-items: center; gap: 10px;"> <div style="border: 1px solid black; border-radius: 10px; padding: 5px 15px;">SPE</div> — <div style="border: 1px solid black; border-radius: 10px; width: 30px; height: 20px;"></div> — <div style="border: 1px solid black; border-radius: 10px; padding: 5px 15px;">OR</div> <div style="border: 1px solid black; border-radius: 10px; width: 30px; height: 20px;"></div> </div> <p>e.g. SPE-10-20BB</p>			

Packaging	4⅝"	9¾"	20"	30"	40"	9¾"BB	20"BB
	30 at 5kg	15 at 3kg	15 at 5kg	15 at 8kg	15 at 9kg	6 at 3kg	6 at 5kg

Features & Information

- An economic, versatile and high flow capability pre-filter
- The large surface area of the Pleat² creates a filter with superior dirt-holding capacity
- Cartridges are formed around a polypropylene core, with the polyester media secured by bonded vinyl plastisol end caps to ensure filter integrity
- Available in large diameter 9¾" and 20" lengths for reduced cartridge change-out frequency
- Flow rate, pressure drop and efficiency data available online