

DATA SHEET SWISSCAVE WL355DF

Technical Data

| Exterior | |
|---|--|
| Casing | Black coated steel |
| Door glazing | Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (3-layer glazing) |
| Door frame | Filigree edging made of black anodised, brushed aluminium |
| Door handle | Black anodised, brushed aluminium (rectangular) |
| Door lock | Yes |
| Door hinge | Right |
| Door hinge convertible as option (right to left) | Yes |
| Product dimensions without door handle (H/W/D) | 1270 x 595 x 710 mm |
| Packaging dimensions (H/W/D) | 1420 x 645 x 777 mm |
| Interior | |
| Temperature zones | 2 |
| Lighting | Blue ceiling lighting |
| Lighting on/off switch | Yes |
| Number of shelves total | 4 |
| Number of display shelves (for perfect wine presentation) | 1 (other shelf types) |
| Number of bottle levels max. | 11 |
| Shelf material | Beech wood |
| Telescopic shelves on extendable steel ball bearings | Full extension shelves (80%) |
| Inside casing | Black PUR/ALU |
| Scope of functions | |
| Optimal usage | Long-term storage |
| User interface | 2 digital displays (set and actual temp.) |
| Active carbon filters (ensuring optimal air quality) | Yes |
| Compressor | JP-STD |
| Coolant | R600a (environment friendly) |
| Vibrationfree implementation | Yes |
| Cooling system | Combined fan and convection cooling |
| Defrost function | Automatic |
| Temperatur Memory Function (Power failure) | Yes |
| Condensation water container | Yes |
| Heating | Yes (integrated powerful winter function) |
| Acoustic temperature alarm | Yes |
| Acoustic door alarm | Yes |
| Feet adjustable to compensate uneven floors | Yes |

| Performance data | |
|---|--|
| Bottle capacity (Bordeaux shape, part of shelves removed) | 135 |
| Bottle capacity (Bordeaux shape, all shelves inserted) | 112 |
| Space for oversized bottles (Magnum, 3lt.) | On top and bottom shelf |
| Humidity | 50 - 70% depending on ambient humidity |
| Climate classification | SN / ST |
| Volume | 261 l |
| Noise level | 40 dB(A) sound-absorbing recommendation |
| Temperature range upper zone | 5 °C - 16 °C |
| Temperature range lower zone | 9 °C - 20 °C |
| Temperature delta between zones | 1 °C - 2 °C |
| General Information | |
| Cooler shape | Freestanding or built-in with shadow gap |
| Maintenance contract (warranty extension) | Recommended |
| Transport weight | 78 kg |
| Net weight | 73 kg |
| Power consumption per day | 0,471 kWh (ca.) |
| Voltage | 240 V / 50 Hz |
| Cable length | 1.5 m |

