

DATA SHEET SWISSCAVE WLB-160F

Technical Data

Exterior	
Casing	Black coated steel
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed)
Door frame	Filigree edging made of black anodised, brushed aluminium
Door handle	Black anodised, brushed aluminium (rectangular)
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	820 x 595 x 595 mm
Packaging dimensions (H/W/D)	865 x 650 x 655 mm
Interior	
Temperature zones	1
Lighting	White all-round lightning
Lighting on/off switch	Yes
Number of shelves total	5
Number of display shelves (for perfect wine presentation)	0 (optionally available)
Number of bottle levels max.	7
Shelf material	Beech wood
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)
Inside casing	Black PUR/ALU
Scope of functions	
Optimal usage	Long-term storage
User interface	2 digital displays (set and actual temp.)
Active carbon filters (ensuring optimal air quality)	Yes
Compressor	Embraco Fullmotion (speed-controlled)
Coolant	R600a (environment friendly)
Vibrationfree implementation	Yes
Cooling system	Combined fan and convection cooling
Defrost function	Automatic
Temperatur Memory Function (Power failure)	Yes
Condensation water container	Yes
Heating	Yes (integrated powerful winter function)
Acoustic temperature alarm	Yes
Acoustic door alarm	Yes
Feet adjustable to compensate uneven floors	Yes

Performance data	
Bottle capacity (Bordeaux shape, part of shelves removed)	55
Bottle capacity (Bordeaux shape, all shelves inserted)	47
Space for oversized bottles (Magnum, 3lt.)	On top and bottom shelf
Humidity	50 - 70% depending on ambient humidity
Climate classification	SN
Volume	127 l
Noise level	36 dB(A) sound-absorbing recommendation
Temperature range	5°C - 20°C

General Information	
Cooler shape	Freestanding or built-in with shadow gap
Maintenance contract (warranty extension)	Recommended
Transport weight	53 kg
Net weight	49 kg
Power consumption per day	0.27 kWh (ca.)
Voltage	220 V / 50 Hz
Cable length	1.5 m

