

PRO-C SERIES

/\\/_P(:

Model	MV-PC
Panel	Type: LCD
Resolution	4K
Brightness (Typ.)	700+ Nits
Contrast Ratio (Typ.)	4000:1
Viewing An- gle (H / V)	178:178
Orientation	Landscape / Portrait
Operation Hour	24/7
Sound	Built-In



43"

49"

55"

37.7"W x 21.6"H x 1.1"D 43"W x 24.5"H x 1.1"D 48.3"W x 27.6"H x 1.1"D

Our MirageVision Pro-C models are designed for commercial outdoor digital signage. The donor display is a commercial digital sign (PH-F series) by Samsung that is made for 24/7 usage with built-in media player and an upgraded anti-glare screen. These models have been altered for outdoor use and are rated at 700+ Nits of brightness - before our added MPET outdoor calibration that enhances the brightness, color, gamma and contrast for outdoor daytime viewing. Thin bezel design for video wall applications.

FEATURES

WEATHER PROOF

Diamond Pro-C DS's are IP5x certified, signifying their dustresistant design and ability to withstand a range of environmental conditions.

The all-new embedded media player powered by TIZEN™ Transcending past hardware performance, the new SSSP 4.0 enables CMS partners to develop and deploy advanced web applications which can help to effectively manage content and SMART Signage.

SLIM DESIGN

Boasting of the slimmest depth design in the industry (29.9mm), Diamond-Pro-C DS displays provide a compact, but strong signage solution for environments limited by space or configuration.

24/7 CONTINUOUS OPERATION

Commercial-level cooling techniques offer dependable reliability. Samsung QMF displays are designed to deliver peace of mind.

NON-GLARE PANEL

The non-glare panel minimizes reflection, making messages easier to see. Text is legible, visuals have maximum impact.

Connectivity DVI-I (D-Sub Common), DisplayPort RGB 1.2 (2) Video HDMI (4) Audio Stereo Mini Jack LISB USB Output Stereo Mini Jack Audio External R2232 Control External Sensor Power Type: Internal Power Sup-AC 100 - 240 V~ (+/- 10 %), 50/60 Hz ply Features VESA Mount: 400 x 400mm Stand Type NO, Must be Wall Mounted Temperature Sensor, Pivot Display, Hardware Clock Battery (80hrs. Clock Keep ing), Built in Speaker (10W 2ch), IP5x Environmental Operating Temperature: 0°C ~ 40°C Conditions Optional Green Man-Emission Standard: EMC agement **Energy Star ENERGY STAR 7.0** Compliant RoHS Compliant Packaging Packing Materials Recyclable Recyclability Contrast MEGA Humidity Circuitry and Boards Coated with out Krytpo-Shield™ Technology Protection Weatherproof YES. Must be used when TV is not Cover

Samsung Digital Sign Donor

SPECIFICATIONS

WARRANTY

Donor

ONE (1) YEAR RESIDENTIAL PARTS AND LABOR LIMITED WARRANTY WITH THE 2ND YEAR AT 25% OF THE INVOICE FOR REPLACEMENT AND 3RD YEAR AT 50% OF THE INVOICE FOR REPLACEMENT. ONE (1) YEAR COMMERCIAL PARTS AND LABOR LIMITED WARRANTY.