

Part No.

LC20-GP2M-00-00

LC20 pressure gauge, 1000 psi / 7 MPa, 1/4" Male NPT bottom connection

The LC20 is a robust device that measures and displays pressure readings on a large, backlit screen. The LC20 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC20-GP2M-00-00

Specs/Attributes

| | |
|-----------------------------|--|
| Battery Count | 2 |
| Battery Life | 1000 Hours |
| Battery Type | AA Alkaline (IEC-LR6) |
| Calibration Certificate | NIST traceable (included) |
| Certifications | Certified to CSA Standard C22.2 No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU |
| Country of origin | USA |
| Datalogging | PC based (via USB) |
| Electrical Rating | 50 mA @ 5 VDC |
| Harmonized Code | 9026.20.0000 |
| Ingress Protection | IP67 (1 meter water submersion for 30 minutes) |
| LCD Display | 2.4 in / 61 mm segmented LCD Display |
| Materials | ABS / Polycarbonate Blend, Powder Coated Aluminum |
| Max Operating Temperature | 120 °F / 50 °C |
| Media Compatibility | Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Min Operating Temperature | -4 °F / -20 °C |
| Panel Mount | No |
| Primary Power | Battery Power |
| Process Connection | 1/4" Male NPT (ASME B1.20.1) |
| Process Connection Location | Bottom mount |
| Protection Class | Pollution Degree 2 (UL / IEC 61010-1) |

Specs/Attributes

| | |
|--------------------------|---|
| Temperature Compensation | None |
| USB Connection | USB (Micro B) |
| W1 Radio Installed | No |
| Wetted Materials | 316 Stainless Steel |
| Weight | 12.6 oz / 355 grams |
| Dimensions | H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm) |

Sensor A (Bottom)

| | |
|---------------------------------|---|
| Sensor Type | Pressure Sensor |
| Wrench Size | 7/8 In 23 mm |
| Max Storage Temperature | 165 °F / 75 °C |
| Min Storage Temperature | -40 °F / -40 °C |
| Measurement Type | Gauge Pressure |
| Max Pressure | 1000 PSI / 70 bar / 7.00 MPa |
| Wetted Materials | 316 Stainless Steel |
| Country of origin | USA |
| Burst Pressure | 4000 PSI / 275 bar / 28 MPa |
| Media Compatibility | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water |
| Accuracy - Pressure Measurement | +/- 0.1% of Full Scale (ASME B40.100 Grade 4A/ISO Class 0.1) |
| Engineering Units | atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, mbar, psi, inHg @39°F, kgf / cm ² , mmHg @0°C, Torr, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / in ² |
| Max Operating Temperature | 120 °F / 50 °C |
| Min Operating Temperature | -4 °F / -20 °C |
| Process Connection | 1/4" Male NPT |