

Part No.

# QTCM-0000-0-0

*QTCM manifold only, no gauge adapter, no hoses, no process connections, no bag*

The most economical way of performing static pressure calibrations in the field using nitrogen or other compressed gas.



QTCM-0000-0-0

## Included Items

- Manifold - QTCM Brass Calibration Manifold (QTCM)

## Specs/Attributes

Max Pressure	3000 PSI / 200 bar / 20 MPa
Materials	Brass
Seal Materials	Buna-N, Delrin, Teflon
Min Operating Temperature	0 °F / -18 °C
Max Operating Temperature	130 °F / 54 °C
Hose 1	None
Hose 2	None
Pressure Reference	None
Process Connection	None
Reference Connection	None
Country of origin	USA
Weight	1.46 lbs / 660 grams
Dimensions	H: 3.78 in (9.6 cm) x W: 5.16 in (13.11 cm) x D: 2.63 in (6.68 cm)

## Manifold QTCM

Max Pressure	3000 PSI / 200 bar / 20 MPa
Min Operating Temperature	0 °F / -18 °C

**Manifold QTCM**

Max Operating Temperature	130 °F / 54 °C
Fine Adjustment Resolution	0.10 PSI / 0.69 mbar / 0.00 kPa
Country of origin	USA
Pressure Media	Nitrogen, inert gas
Inlet Port	Male Quick-test
Materials	Anodized Aluminum, Brass
Media Compatibility	Air, Inert Gas, Natural Gas
Outlet Port	Male Quick-test
Seal Materials	Buna-N, Delrin, Teflon
Burst Pressure	12000 PSI / 825 bar / 83 MPa
Weight	2.20 lbs / 1000 grams
Dimensions	H: 3.8 in (9.65 cm) x W: 5.1 in (12.95 cm) x D: 2.3 in (5.84 cm)