

Illumination gaps at top and bottom of fitting

**ENERGY LABEL**  
ENERGY CLASS: **A<sup>+</sup>**  
Eterna 284S15LED  
6.00 kWh/1000h

**Eterna** LEDSHDVO

This luminaire is compatible with bulbs of the energy classes:

This luminaire is sold with a bulb of the energy class: **A<sup>+</sup>**


874/2012



**LED DUAL VOLTAGE SHAVER LIGHT**

- Requires 1 x S15 284mm double ended tubular lamp (284S15LED included). Fitting is rated at 60W max
- This luminaire is compatible with bulbs of the energy classes: A+ to E and is sold with a bulb of the energy class: A+
- Polycarbonate construction
- Low energy consumption and prolonged lamp life
- High CRI ≥80: minimises colour distortion of illuminated objects
- Dual voltage shaver socket
- 6W = 400 lumen output
- Instant start, super bright LED's, 3000K warm colour temperature: offering a pleasing light appearance
- Safety isolating transformer: for bathroom use
- Mains isolation upon diffuser removal
- **NOTE:** the shaver socket will only operate when the light is switched on

- **Fitting** = M.O.M: 1 / O.P.Q: 10
- **Lamp** = M.O.M: 1 / O.P.Q: 30



Code	Version	Wattage	Colour	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating	Energy Rating
LEDSHDVO	Fitting	6W	White	3000K	400 lm	15,000 hrs	IP20	A <sup>+</sup>
284S15LED	Lamp	6W	White	3000K	400 lm	15,000 hrs	-	A <sup>+</sup>

**LED LAMP SPECIFICATIONS:**

Lumens total flux	<b>400 lm</b>
Rated Wattage	6W
Rated luminous flux	400 lm
Nominal life time of the lamp	15,000 hrs
Colour temperature	3000K
Number of switching cycles before premature lamp failure	100,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
Lamp dimensions (mm)	284 x 25mm
Nominal beam angle	>120°
Rated power	6W
Rated lamp lifetime	15,000
Lamp power factor	>0.5
Lumen maintenance factor at end of nominal life	>70%
Starting time	<0.5s
Colour rendering	>80
Colour consistency	Within 6 step Macadam ellipse
Rated beam angle	>120°
Cap type	S15
Voltage	240V

