

12V CONTROLLERS FOR G510 & G242 RANGE



Control for the 12V safety Extra Low Voltage fans is to be made by a mains transformer unit with SELV output. These controllers must only be fitted outside zone 2 of a bathroom. Please refer to IET Wiring Regulations for guidance. Each controller is supplied complete with a 25mm deep surface pattress box. Units cab alternatively be flush wall mounted if desired.

- Neon indicator fitted to all models



12VFC



12VFCT



12VFCFS

	12VFC	12VFCT	12VFCFS
Product Finish	White	White	White
Description	12V Controller	12V Controller with fitted overrun timer Timer is adjustable between 2-30 mins	12V Controller with fitted overrun timer and automatic humidstat Humidstat automatically switches on at 70% relative humidity
Product Dimensions	H80 x W145 x D55mm	H80 x W145 x D55mm	H80 x W145 x D55mm
Product weight	631 gms		
Barcode	5012739612244	5012739612282	5012739612251
IP Rating	IP30	IP30	IP30
Class	II double insulated	II double insulated	II double insulated
Output	12V ~ 50Hz, 30W Max SELV	12V ~ 50Hz, 30W Max SELV	12V ~ 50Hz, 30W Max SELV
Guarantee	1 Year	1 Year	1 Year
Certification & Conformity	BS EN60335-1:2002 BS EN 60335-2-80:2003	BS EN60335-1:2002 BS EN 60335-2-80:2003	BS EN60335-1:2002 BS EN 60335-2-80:2003

