

Data Specification Sheet ROTARY ISOLATOR SWITCHES



Code	IN0025	IN0026	IN0027
Rated Current	20A	32A	63A
Description	Rotary 4 Pole Isolator Switch		
Overall dimensions H, W, D, TD (mm)	H=125 W=100 D=86 TD=121	H=125 W=100 D=86 TD=121	H=175 W=115 D=100 TD=135
Fixing Centre (mm)	80 x 80	80 x 80	90 x 90
Product Weight (grams)	0.475Kg	0.475Kg	0.675Kg
Maximum Rated Voltage	600V	600V	600V
Resistance to Surge Pulse Voltage	6KV		
Class	Class I		
Number of Poles	4		
Earth Connections	2		
Lock Facility	Yes (Padlock not supplied)		
Cover Interlock	Yes in ON position		
Recommended product location	Indoor or Outdoor		
Construction	ABS/Polycarbonate		
IP	IP65		
Cable Entry/Knockouts	2 x 20/25mm Top. 2 x 20/25mm Bottom		
Instruction sheet	Yes		
Origin of manufacture	China		
CE mark	Yes		
Batch coding details on product	Yes		
Certificate of Conformity (Held on File)	Yes		
Warranty (Years)	1		
Manufactured & Tested to	IEC60947-1 & 3 EN60947 VDE 0660-107		
EAN	IN0025	IN0026	IN0027
	5055832903802	5055832903833	5055832903963

FRONT

SIDE

BOTTOM/TOP

