

# 7L vented water storage heaters

- An economical solution to provide stored hot water
- EcoT model contains an integral timer
- Minimal standing heat loss as they are installed at point of use
- 1kW model ideal for energy saving and 3kW model ideal for fast recovery and heat time











# **Key Features**

- 7 litre capacity, point of use
- 300mm swivel spout included
- Wall bracket and full fixing pack supplied
- Can be mounted undersink using the monoblock chrome-mixer accessory
- Adjustable thermostat 15°C 75°C with frost protection setting
- Integral safety over-temperature thermal fuse
- Optional tamper proof cover supplied
- 24 hour, 7 day programmable timer on WS7-EcoT model
- 2 year UK guarantee

### **Technical Specification**

- kW loading at 240V: 1 or 3kW
- Cold water 15mm compression
- Outlet ½ BSP swivel spout connection supplied
- Restrictors supplied to optimise flow
  rete
- High quality impact resistant ABS cover
- Sheathed heating elements
- Operating pressure 0.7 bar 10 bar
- NB: we recommend the use of the Redring Vented Monoblock Mixer

#### **Dimensions**



# **Product Range**

Product Ref.	Finish	Model	Cat No.
WS7-EcoT 3kW	White	WS7-EcoT	44780005
WS7 3kW	White	WS73	44780001
WS7 1kW	White	WS71	44780002

Product Ref.	Finish	Model	Cat No.
Extended Swivel Spout 450mm	Chrome	S1	84780404
Extended Swivel Spout 600mm	Chrome	S2	84780405
Monoblock Chrome Vented Mixer	Chrome	MCM	84780408