


EST. 2012




WELLES Glass Long Chandelier 14 in Satin Brass & Alabaster White A new type of modular elegance, the Welles bridges feminine and masculine sensibilities for a perfect blend of strength and sophistication.

Each one of a kind glass piece is mold-blown to generate a gem like form and create a bright diffused light. Polished prong-like hardware boldly supports each glass volume and holds the body of the overall organic silhouette.

All Gabriel Scott pieces are handmade in Canada.





SPECIFICATIONS

Standard Finishes:

Glass: Alabaster White or Smoked Gray

Metal: Satin Nickel, Satin Copper, Satin Brass, Satin Bronze or Blackened Steel

Specifications:

Dimensions: 66.5" x 18.9" x 17.55" H + Drop

 $169 \,\mathrm{cm}\,\mathrm{x}\,48 \,\mathrm{cm}\,\mathrm{x}\,45 \,\mathrm{cm}\,\mathrm{H} + \mathrm{Drop}$

Weight: 5 lbs / 2.27 kg per cube

Light Source: 12V 6 Watt LED (included)

LED Drivers: E60L12DC-KO - 110V UVC1250TD - 220V

Total Wattage (nominal): 43.4 w Lumens (total): 9520 lm

Cables & Canopies:

Cable Length: 96" / 244 cm Drop, adjustable upon installation

(increased cable-lengths available upon request)

Standard Canopy: 5" x 0.5" / 12 cm x 1.3 cm

Deep Canopy: Available upon request.

Custom finishes available upon inquiry.

Made and assembled in Canada. Item is UL & CE listed.



STANDARD FINISHES



Alabaster White & Satin Nickel

Alabaster White & Satin Copper

Alabaster White & Satin Brass



Alabaster White & Satin Bronze

Alabaster White & Blackened Steel



Smoked Gray & Satin Nickel

Smoked Gray & Satin Copper

Smoked Gray & Satin Brass




Smoked Gray & Satin Bronze


Smoked Gray & Blackened Steel

LED DRIVER

E60L12DC-KO - 110V

Magnitude's E60L12DC-KO dimmable voltage LED driver is class 2 rated and designed to operate with any standard MLV/ Incandescent TRIAC (Leading edge) dimmer switch. Encased in a low prole aluminum enclosure that includes 2 knockouts to enable easy installation makes it the perfect choice for under cabinet lights, tape lights and various LED fixtures installations. Our electrical specication includes Auto Reset, over current and short circuit protection. Efficiency of 90% and higher allows the driver to operate at low temperatures.





Features:

- Dimmable with any standard MLV/Incandescent TRI-AC- (Leading edge) dimmer switch.
- Super compact ALUMINUM CASE.
- Class 2
- UL 8750
- IP67 Withstands wet and salty conditions.
- Nema 3R Outdoor Use
- Auto-Reset Protection for short circuits & over-voltage.
- FCC 15 part 2
- 12V DC True RMS

Specifications:

Max Load	60W
Input Voltage	120V AC
Input Current at Max Load	0.61 A
Output Voltage	12V DC
Output Current at Max load	5.26 A
Power Factor	0.95
Efficiency	> 90 %

Operating Temp. -20c - 70c (-4F -158F)

Short Circuit Protection Yes

Overcurrent Protection Yes

Over Temperature Yes

Open Circuit Protections Yes

Input Wires (White / Black) 14 AWG


Output Wires (Red / Black) 18 AWG

Weight 481g

Dimensions (inches) $6.77^{\circ} \times 2.67^{\circ} \times 1.26^{\circ}$ Dimensions (cm) $17.2 \text{ cm} \times 6.8 \text{ cm} \times 3.2 \text{ cm}$

LED DRIVER

UVC1250TD - 220V





Features:

- Constant voltage output
- Fully isolated
- Short circuit, over current and over voltage protection up to 80% efficient.
- · Fire resistant plastic cover
- Compatible with leading and trailing edge dimmers
- 20 ~ 100% Dimming Load and Dimming range
- Mains dimmable
- Screw terminals
- IP44 design for indoor use
- 2 years warranty

Specifications:

Part Code UVC1250TD UVC2450TD

 Voltage
 220V ~ 240VAC

 Frequency
 50-60 Hz

 Current
 0.4A

 Inrush Current
 <2.5A</td>

 Power Factor
 0.95

 Load Voltage
 12V

 No Load Voltage
 12V

 Current
 4.16A

 Power
 50W

 Power Factor
 >0.95

 Efficiency (TYP.)
 >80%

Over Load Auto-recovery
Short Circuit Auto-recovery
Over Voltage Auto-recovery
Operating Temperature -20 ~ +50°C
Storage Temperature -40 ~ +70°C
Relative Humidity 5 ~ 95%

Lifetime 50K hrs at TC max (85°C)
Connections Screw terminal on I/P & O/P

Weight 200g

Dimensions (inches) 7.2" x 2.4" x 1.25"

Dimensions (cm) 18.4 cm x 6 cm x 3.2 cm