



HB03 UFO HIGH BAY SERIES



The high-performance Korlite HB03 LED High Bay Series is ideal for new construction or replacement of 250-1000 watt traditional HID, HPS or CFL fixtures. Delivers top energy savings and maintenance free durability for a wide range of applications: Warehouses and storage, Industrial facilities, Retail centers, Manufacturing, Sports facilities and Gymnasiums.



Features:

- Advanced aluminum heat sink for enhanced air flow, lower operating temperature and top efficiency. Provides 50-70% energy savings.
- Designed for quick, easy installation. Preinstalled hook mount with locking bolt and safety cable for suspension. Optional U-Bracket. Each unit comes with 8' quick connect cord and plug or optional whip. Can be removed for hardwiring.
- Excellent color rendition compared to HID/HPS with uniform 120° beam illumination.
- IP 66 rated: Corrosion proof coating, fully sealed, resistant to dust or low pressure water jets.
- Certified Quality: DLC Premium eligible for rebates / L70 50,000 hour long life, 5 Year Warranty.
- Increase energy savings with optional integrated PIR sensor. Can be adjusted from the ground via remote control: Brightness, Sensitivity, Hold-time, Daylight Harvesting, Stand by dim/time.



HB03 UFO HIGH BAY SERIES



Specifications:

MODEL #:	RKRH0301100W5KD[N;P]LHL	RKRH0301150W5KD[N;P]LHL	RKRH0301200W5KD[N;P]LHL	RKRH0301250W5KD[N;P]LHL
Wattage:	100 Watt	150 Watt	200 Watt	250 Watt
Lumen Output:	15,000	22,500	30,000	37,500
Efficacy:	150 LM/W	150 LM/W	150 LM/W	150 LM/W
*Equivalent to:	250W-400W	400W	400W-600W	750W-1000W
Input Voltage:	120-277V	120-277V	120-277V	120-277V
Power Factor:	> 0.9	> 0.9	> 0.9	> 0.9
THD:	≤ 20%	≤ 20%	≤ 20%	≤ 20%
CCT:	5000K	5000K	5000K	5000K
CRI:	> 70	> 70	> 70	> 70
Mounting:	L-Hook, U-Bracket	L-Hook, U-Bracket	L-Hook, U-Bracket	L-Hook, U-Bracket
Dimmable:	0-10V Constant Current	0-10V Constant Current	0-10V Constant Current	0-10V Constant Current
Operating Temp:	-40°C to 45°C	-40°C to 45°C	-40°C to 45°C	-40°C to 45°C
Lifetime:	> 50,000 hr	> 50,000 hr	> 50,000 hr	> 50,000 hr
Weight:	7 lbs	7 lbs	10.5 lbs	10.5 lbs
Dimensions:	11.62" x 6.81"	11.62" x 6.81"	12.95" x 7.83"	12.95" x 7.83"
Warranty:	5 Years	5 years	5 years	5 Years
Certifications:	DLC Premium, UL	DLC Premium, UL	DLC Premium, UL	DLC Premium, UL

Notes: * Subject to Mounting Height / Units are IP65 when used with PIR Sensor / DLC ± 10% based on installed environment. DesignLights Consortium® www.designlights.org