

# NEW OZ TIMBER FLOORING

## **TEST REPORT**

## **REPORT NUMBER**

180814010SHF-BP-1

## **ISSUE DATE**


2018/9/10

#### **PAGES**

4

## **DOCUMENT CONTROL NUMBER**

LFT-APAC-SHF-OP-10a
© 2018 INTERTEK





Intertek Testing Services Ltd., Shanghai Plant 5, No. 6958 Daye Road, Fengxian District, Shanghai, China Tel: 021-61136116 Fax: 021-61189921

Website: www.intertek.com

## **Test Report**

Issue Date: 2018/9/10 Intertek Report No. 180814010SHF-BP-1

Applicant: NEW OZ TIMBER FLOORING

Applicant Address: 2/262 PARRAMATTA ROAD GRANVILLE, 2142 NSW AUSTRALIA

**SUBJECT:** Performance testing

Stone Floor

Dear Sir,

This test report represents the results of our evaluation of the above referenced product(s) to the requirements contained in the following standards:

TEST METHODS AND STANDARDS
Refer to the next following Pages.

SAMPLE ID	MODEL	SPECIFICATION
S180814010SHF.001	1600*180*8.0mm	/

SAMPLE RECEIEVED: 2018/8/13

TESTED FROM: 2018/8/14 TO 2018/9/10

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



## **Test Report**

Issue Date: 2018/9/10 Intertek Report No. 180814010SHF-BP-1

## **Test Items, Method and Results:**

Test Item: Formaldehyde content test

Test Method: With reference to EN 717-1:2004 chamber method, formaldehyde content was detected by UV-VIS spectrophotometer.

Test condition:

Chamber type: 1 m³ stainless steel chamber

Climatic conditions: 23°C, 45% R.H.

Air exchange rate:  $1.0 \text{ h}^{-1}$ Loading factor:  $1.0 \text{ m}^2/\text{m}^3$ Test duration: 222 hours

Test result: ND

#### Note:

1. mg/m<sup>3</sup> = milligram per cubic meter

2. ND = Not Detected

3. Detection limit =  $0.02 \text{ mg/m}^3$ 



## **Test Report**

Issue Date: 2018/9/10 Intertek Report No. 180814010SHF-BP-1

**APPENDIX: SAMPLE RECEIVED PHOTO** 



## **REPORT AUTHORIZED**

When signed with physical or electronic signature, the contents of this report have been prepared and approved per Intertek's quality process in accordance with ISO 17025.

Flora Far

Title: Reviewer

盆检测专用章 ( Project Engineer

## **Revision:**

NO.	DATE	CHANGES	AUTHOR	REVIEWER
180814010SHF-BP-1	2018/9/10	First issue	Grace Wang	Flora Fan