



CDC264J

RCCB 2P 63A 30mA AC

Technische Merkmale

Architecture

Neutral position	right
Number of poles	2 P
Fixing mode	Din-Rail

Controls and indicators

Ground fault signalisation	no
With fault indicator	yes

Main electrical features

Frequency	50 Hz
-----------	-------

Electric current

Rated residual operating current	30 mA
Withstand not tripping on 8-20 μ s wave	0,25 kA
Breaking and opening capacity	1500 A
Rated conditional short-circuit current I_{nc} according to EN 61008-1	6 kA

Electric current / temperature

Rating current -15°C	63 A
Rating current -20°C	63 A
Rating current 0°C	63 A
Rating current 10°C	63 A
Rating current -10°C	63 A
Rating current 15°C	63 A
Rating current 20°C	63 A
Rating current 25°C	63 A
Rating current -25°C	63 A
Rating current 30°C	63 A
Rating current 35°C	63 A
Rating current 40°C	63 A
Rating current 45°C	63 A
Rating current 5°C	63 A
Rating current -5°C	63 A
Rating current 50°C	63 A
Rating current 55°C	63 A
Rating current 60°C	56 A
Rating current 65°C	49 A
Rating current 70°C	40 A

Power

Power loss per pole at I_n	4,1 W
Total power loss under I_N	8,1 W

Tripping

Short-time delayed tripping	no
Protected against nuisance tripping	no

Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	4000

Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	35 mm
Construction size (DIN 43880)	1

Installation, mounting

Type of bottom rail clip for modular devices	plastic
Type of top rail clip for modular devices	NA
Bottom removability for modular devices	yes
Top removability for modular devices	no

Connection

Type of connection	with screw
--------------------	------------

Standards

Standard text	IEC 61008-1
European directive WEEE	not concerned

Safety

Protection index IP	IP20
Residual current type	AC

Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Altitude	2000 m
Storage temperature	-55 to 70 °C