# Temperature Humidity Meter

G9400 Series - G9401

The Gazelle G9401 humidity meter features a large triple display of indoor measurements of relative humidity, temperature, and external secondary temperature with maximum and minimum readings. The remote temperature probe extends for 1 meter to measure behind walls, inside refrigerators or to soak into water. Ideal for use in humid areas where mold can become a problem. The meter has a built-in stand for sitting on a desk but can also be mounted to a wall with an additional clock and alarm clock function.



CE

- Sampling time: 10s
- Hanging hole and tripod are available for wall or table mount
- Display of temperature, humidity, time, and comfort level together
- Dual temperature measurement
- Clock function: 12/24 hour modes
- Alarm clock: Rings up to 60s
  Comfort level: comfortable, wet, dry

## Standard Accessories
- Operating Manual
- 1.5V AAA Battery

| Specifications | | Range |
|---|---|---|
| Temperature | Range | -10~50°C (14~122°F) |
| | Resolution | 0.1°C (0.1°F) |
| | Accuracy | ±1°C (±1.8°F) |
| External temperature probe | Range | -10~50°C (14~122°F) |
| | Resolution | 0.1°C (0.1°F) |
| | Accuracy | ±1°C (±1.8°F) |
| Humidity | Range | 10~99%RH |
| | Resolution | 1%RH |
| | Accuracy | ±5%RH |
| Features | | |
| Sampling frequency | | 10s |
| Alarm Clock | | √ |
| Battery | | 1*AAA |
| Certification | | CE |