

## Mini Contact Type Thermometer

G9400 Series - G9402

The G9402 dual-input digital thermometer delivers a fast response. Designed to measure two contact temperature inputs simultaneously, whether measuring motors, insulation, pipes, liquids, and wires with industrial standard J, K-type thermocouple temperature sensors. The user friendly-front panel and large, backlit display make it easy to view results from both channels.



- 1 m drop proof
- Maximum/minimum/average
- LCD backlight
- K/J thermocouple probe selection
- Difference measurement: T1~T2
- CE Certified

### Standard Accessories

- Operating Manual
- Temperature Probe
- 1.5V AAA - 3pcs

| Specifications                 | Range      | Best Accuracy |
|--------------------------------|------------|---------------|
| Temperature measurement (K)    | -50~1300°C | ±(0.5%+1)     |
| Temperature measurement (J)    | -50~1200°C | ±(0.5%+1)     |
| Features                       |            |               |
| Difference measurement (T1-T2) |            | √             |
| Unit conversion (°C/°F)        |            | √             |
| Max/Min/Avg                    |            | √             |
| Function selection (K/J)       |            | √             |
| Backlight                      |            | √             |
| Working temperature            |            | 0°C~40°C      |
| Working humidity (relative)    |            | ≤80%RH        |
| 1m drop test                   |            | √             |
| Power                          |            | 3 x AAA       |