

4P 63A Switch

Technische Merkmale

Architecture

Type of order	Toggle
Neutral position	without neutral
Number of poles	4 P
Type of pole	4 P

Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	415 V

Electric current

Closing ability with 400V in AC23A	1332 A
Rated short-circuit making capacity Icm under 415V AC according IEC 60947-3	1332 A
Thermal rated current outside of housings	63 A

Power

Power loss per pole at In	3,5 W
Total power loss under IN	13,9 W

Endurance

Electrical durability at nominal load in AC21 in operating cycles	2500
Electrical durability at nominal load in AC22 in operating cycles	2500
Number of mechanical operations	4000

Installation, mounting

Bottom removability for modular devices	no
Top removability for modular devices	no

Connection

Cage clamp position	in line
Connection cross-sect. rigid cable	4 / 50mm ²
Connection cross-sect. flexible conductor	2,5 / 16mm ²
Type of connection	with screw

Equipment

Quantity of NO contacts	4
Can be accessorized	yes

Standards

Standard text	IEC 60947-3
European directive WEEE	not concerned

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Altitude	2000 m
----------	--------

Storage temperature	-40 to 80 °C
---------------------	--------------
