



EH010



Daily time switch 1 channel, 16A, 1 module

Technical characteristics

Architecture

Fixing mode	Din-Rail
-------------	----------

Configuration

Switch mode	NO contact
-------------	------------

Main electrical features

Frequency	50 Hz
-----------	-------

Voltage

Supply voltage	230V AC
----------------	---------

Dimensions

Depth of installed product	60 mm
----------------------------	-------

Height of installed product	80 mm
-----------------------------	-------

Width of installed product	18 mm
----------------------------	-------

Dimensions (W x H x D)	18 x 80 x 60 mm
------------------------	-----------------

Power

Power consumed	0,5 VA
----------------	--------

Power consumption (operation)	0,5 VA
-------------------------------	--------

Total power loss under IN	1 W
---------------------------	-----

Power dissipation per coil	0,5 W
----------------------------	-------

Capacity

Breaking capacity	16A 250V AC1
-------------------	--------------

Capacity

Number of modules	1
-------------------	---

Incandescent bulbs control

Max. power with incandescent lamps	900 W
------------------------------------	-------

Installation, mounting

Mounting type	din-Rail
---------------	----------

Connection

Connection cross-sect. flexible conductor	1 / 6mm ²
---	----------------------

Connection cross-sect. rigid cable	1,5 / 10mm ²
------------------------------------	-------------------------

Type of connection	with screw
--------------------	------------

Number of contacts	1
--------------------	---

Type of contacts	1 changeover
------------------	--------------

Type of connection	with screw terminals
--------------------	----------------------

Settings

Summer / Winter time change	manual
-----------------------------	--------

Shortest switching time	15 mn
-------------------------	-------

Type of programming	analog
---------------------	--------

Programming cycle	24H
Setting	Setting via day dial
Equipment	
Number of channels	1
Supply failure reserve	without
Use	
Cycle	daily
Safety	
Protection index IP	IP20
Use conditions	
Operating temperature	-10...55 °C
Working accuracy	1