

SAFETY DATA SHEET

01 January 2017

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION		
PRODUCT NAME:	Phil Waterproof Grease	
PRODUCT NUMBER(S):	GPD120, GPD480, GPJ000, GPL000, GPP100, GPP200, GPP500, GPS000, GPT000	
COMPANY IDENTIFICATION:	Phil Wood & Co. 1125 North 7 th Street San Jose, CA 95112 United States of America Telephone: 408 298-1540 Fax: 408 298-9016 Email: sales@philwood.com EMERGENCY PHONE NUMBER: CHEMTREX EMERGENCY RESPONSE 1-800-424-9300	
RECOMMENDED USE:	General Bicycle, Chain, Cable, and Bearing Lubricant.	
SECTION 2: HAZARD(S) IDENTIFICATION		
CLASSIFICATION:	Acute aquatic toxicant: Category 3. Chronic aquatic toxicant: Category 3.	
ENVIRONMENTAL HAZARDS:	Harmful to aquatic life with long lasting effects.	
PRECAUTIONARY STATEMENTS:	Prevention: Avoid release to the environment. Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international regulations.	
HAZARDS NOT OTHERWISE CLASSIFIED:	Not Applicable	
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS		
COMPONENTS	CAS NUMBER	AMOUNT
Highly refined mineral oil (C15-C50)	Mixture	70-99 % weight
SECTION 4: FIRST-AID MEASURES		
DESCRIPTION OF FIRST AID MEASURES:	Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water. Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, apply a waterless hand cleaner, mineral oil, or petroleum jelly. Then wash with soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse. Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice. Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.	
MOST IMPORTANT SYMPTOMS AND EFFECTS:	IMMEDIATE HEALTH EFFECTS Eye: Not expected to cause prolonged or significant eye irritation. Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. High-Pressure Equipment Information: Accidental high-velocity injection under the skin of materials of this type may result in serious injury. Seek medical attention at once should an accident like this occur. The initial wound at the injection site may not appear to be serious at first but, if left untreated, could result in disfigurement or amputation of the affected part. Ingestion: Not expected to be harmful if swallowed. Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil.	

	<p>May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing.</p> <p>DELAYED OR OTHER HEALTH EFFECTS: Not classified. Indication of any immediate medical attention and special treatment needed: Not Applicable.</p>
SECTION 5: FIRE-FIGHTING MEASURES	
EXTINGUISHING MEDIA:	Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.
PROTECTION OF FIRE FIGHTERS:	<p>Fire Fighting Instructions: This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.</p> <p>Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.</p>
SECTION 6: ACCIDENTAL RELEASE MEASURES	
PROTECTIVE MEASURES:	Eliminate all sources of ignition in vicinity of spilled material.
SPILL MANAGEMENT:	Clean up spills immediately, observing precautions in Exposure Controls/Personal Protection section. Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations.
REPORTING:	Report spills to local authorities and/or the U.S. Coast Guard's National Response Center at 1-800-424-8802 as appropriate or required.
SECTION 7: HANDLING AND STORAGE	
GENERAL HANDLING INFORMATION:	Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.
PRECAUTIONARY MEASURES:	Keep out of the reach of children.
STATIC HAZARD:	Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.
CONTAINER WARNINGS:	Containers are not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, and promptly disposed of properly.
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION	
GENERAL CONSIDERATIONS:	Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS:	Use in a well-ventilated area.				
PERSONAL PROTECTIVE EQUIPMENT	<p>Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.</p> <p>Skin Protection: No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: Neoprene, Nitrile Rubber, Silver Shield, Viton.</p> <p>Respiratory Protection: No respiratory protection is normally required. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air purifying respirators use a particulate cartridge. Use a positive pressure air supplying respirator in circumstances where air purifying respirators may not provide adequate protection.</p>				
OCCUPATIONAL EXPOSURE LIMITS:					
COMPONENT	AGENCY	TWA	STEL	CEILING	NOTATION
Highly refined mineral oil (C15 C50)	OSHA Z 1	5mg/m3			
Highly refined mineral oil (C15 C50)	ACGIH	5mg/m3	10mg/m3		
Consult local authorities for appropriate values.					
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES					
Attention: The data below are typical values and do not constitute a specification.					
PHYSICAL STATE:	Semi-solid				
COLOR:	Green				
ODOR:	Petroleum odor				
ODOR THRESHOLD:	No data available				
pH:	Not Applicable				
INITIAL BOILING POINT:	No data available				
FLASHPOINT:	(Cleveland Open Cup) 246 °C (475 °F) (Typical)				
FLAMMABILITY (SOLID, GAS):	No Data Available				
FLAMMABILITY (EXPLOSIVE) LIMITS (% BY VOLUME IN AIR) LOWER:	Not Applicable				
FLAMMABILITY (EXPLOSIVE) LIMITS (% BY VOLUME IN AIR) UPPER:	Not Applicable				
VAPOR PRESSURE:	<0.01 mmHg Maximum @ 37.8 °C (100 °F)				
VAPOR DENSITY (AIR=1):	>1 Minimum				
SOLUBILITY:	Soluble in hydrocarbons; insoluble in water				
OCTANOL/WATER PARTITION COEFFICIENT:	No data available				
VISCOSITY:	11.8 mm ² /s @ 100°C (212°F) Minimum				
DENSITY:	No data available				
EVAPORATION RATE:	No data available				
MELTING POINT:	No data available				
FREEZING POINT:	Not Applicable				

SPECIFIC GRAVITY:	0.9 @ 15.6°C (60.1°F) (Typical)
DECOMPOSITION TEMPERATURE:	No data available
AUTOIGNITION:	No data available
SECTION 10: STABILITY AND REACTIVITY	
REACTIVITY:	May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
CHEMICAL STABILITY:	This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
INCOMPATIBILITY WITH OTHER MATERIALS:	Not applicable
HAZARDOUS DECOMPOSITION PRODUCTS:	None known (None expected)
HAZARDOUS POLYMERIZATION:	Hazardous polymerization will not occur.
SECTION 11: TOXICOLOGICAL INFORMATION	
SERIOUS EYE DAMAGE/IRRITATION:	The eye irritation hazard is based on evaluation of data for product components.
SKIN CORROSION/IRRITATION:	The skin irritation hazard is based on evaluation of data for product components.
SKIN SENSITIZATION:	The skin sensitization hazard is based on evaluation of data for product components.
ACUTE DERMAL TOXICITY:	The acute dermal toxicity hazard is based on evaluation of data for product components.
ACUTE ORAL TOXICITY:	The acute oral toxicity hazard is based on evaluation of data for product components.
ACUTE INHALATION TOXICITY:	The acute inhalation toxicity hazard is based on evaluation of data for product components.
ACUTE TOXICITY ESTIMATE:	Not Determined
GERM CELL MUTAGENICITY:	The hazard evaluation is based on data for components or a similar material.
CARCINOGENICITY:	The hazard evaluation is based on data for components or a similar material.
REPRODUCTIVE TOXICITY:	The hazard evaluation is based on data for components or a similar material.
SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE:	The hazard evaluation is based on data for components or a similar material.
SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE:	The hazard evaluation is based on data for components or a similar material.
ADDITIONAL TOXICOLOGY INFORMATION:	This product contains petroleum base oils which may be refined by various processes including severe solvent extraction, severe hydrocracking, or severe hydro treating. None of the oils requires a cancer warning under the OSHA Hazard Communication Standard (29 CFR 1910.1200). These oils have not been listed in the National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as; carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A), or possibly carcinogenic to humans (Group 2B). These oils have not been classified by the American Conference of Governmental Industrial Hygienists (ACGIH) as: confirmed human carcinogen (A1), suspected human carcinogen (A2), or confirmed animal carcinogen with unknown relevance to humans (A3).
SECTION 12: ECOLOGICAL INFORMATION:	
ECOTOXICITY:	This material is expected to be harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.
MOBILITY:	No data available.
PERSISTENCE AND DEGRADABILITY:	This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. The

	product has not been tested. The statement has been derived from the properties of the individual components.		
POTENTIAL TO BIOACCUMULATE:	Bio Concentration Factor: No data available. Octanol/Water Partition Coefficient: No data available		
SECTION 13: DISPOSAL CONSIDERATIONS			
	Use material for its intended purpose or recycle if possible. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact sales at Phil Wood & Co. or local environmental or health authorities for approved disposal or recycling methods.		
SECTION 14: TRANSPORTATION INFORMATION			
	The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.		
DOT SHIPPING DESCRIPTION:	PETROLEUM LUBRICATING GREASE; NOT REGULATED AS A HAZARDOUS MATERIAL FOR TRANSPORTATION UNDER 49 CFR		
IMO/IMDG SHIPPING DESCRIPTION:	PETROLEUM LUBRICATING GREASE; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE		
ICAO/IATA SHIPPING DESCRIPTION:	PETROLEUM LUBRICATING GREASE; NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER ICAO		
	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable		
SECTION 15: REGULATORY INFORMATION			
EPCRA 311/312 CATEGORIES:	1	Immediate (Acute) Health Effects:	NO
	2	Delayed (Chronic) Health Effects:	NO
	3	Fire Hazard:	NO
	4	Sudden Release of Pressure Hazard:	NO
	5	Reactivity Hazard:	NO
REGULATORY LISTS SEARCHED:			
1-1 =IARC GROUP 1	02=NTP CARCINOGEN	05=MA RTK	
1-2 A=IARC GROUP 2A	03=EPCRA 313	06=NJ RTK	
01-2B=IARC GROUP 2B	04=CA PROPOSITION 65	07=PA RTK	
No components of this material were found on the regulatory lists above.			
CHEMICAL INVENTORIES:	All components comply with the following chemical inventory requirements: IECSC (China), PICCS (Philippines), TSCA (United States).		
NEW JERSEY RTK CLASSIFICATION:	Under the New Jersey Right-To-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Grease)		
SECTION 16: OTHER INFORMATION			
NFPA RATINGS:	Health: 0	Flammability: 1	Reactivity: 0
HMIS RATINGS:	Health: 0	Flammability: 1	Reactivity: 0
(0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *- Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).			
ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:			
TVL – Threshold Limit Value		TWA – Time Weighted Average	

STEL – Short-term Exposure Limit	PEL – Permissible Exposure Limit
GHS – Globally Harmonized System	CAS – Chemical Abstract Service Number
ACGIH – American Conference of Governmental Industrial Hygienists	IMO/IMDG – International Maritime Dangerous Goods Code
API – American Petroleum Institute	SDS – Safety Data Sheet
HMIS – Hazardous Materials Information System	NFPA – National Fire Protection Association (USA)
DOT – Department of Transportation (USA)	NTP – National Toxicology Program (USA)
IARC – International Agency for Research on Cancer	OSHA – Occupational Safety and Health Administration
NCEL – New Chemical Exposure Limit	EPA – Environmental Protection Agency
SCBA – Self-Contained Breathing Apparatus	

Prepared according to the 29 CFR 1910.1200 (2012) by Phil Wood & Co. 1125 North Seventh Street San Jose, CA 95112

Phil Wood & Co.