

## SPIKA NG 130

115 V / 60 Hz

### SELF-CONTAINED ICE CUBE MACHINE

#### FEATURES

- ▶ PRODUCES FULL DICE ICE CUBES OR HALF DICE ICE CUBES.
- ▶ STIF: STRONG INOX FRAME. SOLID MACHINE STRUCTURE IN 4 COLUMNS WITH AISI 304 STAINLESS STEEL FRAME.
- ▶ STRONGEST DOOR IN THE MARKET. MADE OF STAINLESS STEEL. OPENING AND DAMPING SYSTEM PATENTED BY ITV.
- ▶ SMART FRONT VENTILATION SYSTEM, (SFVS) ALLOWS BUILT-IN INSTALLATION OF THE UNIT.
- ▶ CLEANING SWITCH: ALLOWS CIRCULATION OF WATER WITH DESCALING PRODUCT (CALKIN OR SIMILAR) WITHOUT COOLING.
- ▶ "NEVER STOP" MOTOR PUMP DEVELOPED BY ITV. PUMP WITHOUT SEALS, WHICH AVOIDS DETERIORATION IN HARD WATER.
- ▶ EASI: EASY ACCESS FOR SERVICE & INSTALLATION. ALL PANELS CAN BE DISASSEMBLED SEPARATELY.
- ▶ ELECTRONIC CONTROL THAT ENHANCES THE PERFORMANCE OF THE MACHINE AND ALLOWS IT TO ADAPT TO EXTREME CLIMATES.
- ▶ NATURAL GAS R290 WITH VERY LOW GLOBAL WARMING POTENTIAL WHICH ALSO REDUCES THE ENERGY CONSUMPTION.
- ▶ LED ON/OFF SWITCH / PCB MOUNTED AT THE BOTTOM.
- ▶ TROPICALIZED MACHINES (T CLASS) / STAINLESS STEEL ADJUSTABLE LEGS.



	24 H	70°F/20°C    50°F/10°C	90°F/32°C    70°F/21°C	<b>lbs (Kg)</b>	<b>in (mm)</b>	<b>in (mm)</b>	<b>SPIKA HALF DICE</b> 0.9" (W) x 0.43" (D) x 1.02" (H) 23 mm (W) x 11 mm (D) x 26 mm (H) Average dimensions
SPIKA NG 130 A		<b>134 (61)</b>	<b>101 (47)</b>	<b>44.1 (20)</b>	Width <b>21.07"</b> (535) Depth <b>23.43"</b> (595) Height* <b>31.07"</b> (789)	Width <b>24.02"</b> (610) Depth <b>25.79"</b> (655) Height <b>35.83"</b> (910)	<b>SPIKA FULL DICE</b> 1.02" (W) x 0.9" (D) x 1.02" (H) 26 mm (W) x 23 mm (D) x 26 mm (H) Average dimensions
SPIKA NG 130 W		-	-				

\* WITH LEGS 35"/37"


#### ACCESSORIES

##### INCLUDED



# TECHNICAL SCHEME

SPIKA NG 130



\* All dimensions in inches (and mm)

## OPERATING CONDITIONS

### PRODUCTION (LBS) 60Hz


±10% V

41°F/109°F

41°F/95°F

14.5 psi (1 bar) / 87 psi (6 bar)

75/150 Ice cubes/cycle



V	Hz	ph
115	60	1N

24 H

FULL DICE  
 SPIKA NG 130 AIR COOLED

°F	50°	60°	70°	86°
10°	15°	21°	30°	
50°	141	130	121	110
10°				
68°	139	126	112	99
20°				
90°	134	112	101	90
32°				
109°	108	82	71	60
43°				

24 H

FULL DICE  
 SPIKA NG 130 WATER COOLED

°F	50°	60°	70°	86°
10°	15°	21°	30°	
50°	-	-	-	-
10°				
68°	-	-	-	-
20°				
90°	-	-	-	-
32°				
109°	-	-	-	-
43°				

## MODELS

SPIKA NG 130 A

SPIKA NG 130 W

	ASHRAE CONDITIONS (BTu/h)	(W)	(W) 109°F	(AWG/mm <sup>2</sup> ) (n.)	FUSE	100lbs 90°F / 70°F (Kwh/100 lbs)	gal 100lbs (l/h)	HEAT REJECTED (BTu/h) (W)	(lbs)	(lbs)			
SPIKA NG 130 A	2,943	862	375	16/1.5	3	16	8.7	22.3	3.6	1,605	470	106	123,5
SPIKA NG 130 W	-	-	-	-	-	-	-	-	-	-	-	-	-



ITV Ice Makers, Inc.  
 9550 Satellite Blvd, Suite 100  
 Orlando, FL 32837  
 Phone: 1 407 826 1860 | Fax: 1 407 826 1861  
 Toll Free: 1 888 488 1423  
 sales@itvice.com | www.itvice.com



SERVICE  
 service@itvice.com  
 Skype: service@itvice.com  
 PHONE: +1 888 488 1423  
 FROM 8AM TO 5PM EST



2 ADDITIONAL YEARS  
 ON COMPRESSOR &  
 EVAPORATOR  
 Read our warranty policy  
 to know more about  
 limitations and exclusions

