

STEALTH 895 NBS™ 2.0



blendtec
COMMERCIAL 2019



THE ORIGINAL QUIET BLENDER

Winner of the National Restaurant Association's prestigious Kitchen Innovations Award, the Stealth 895 NBS combines durability, power and a wealth of exciting features - all designed to save you money.

STEALTH 895 NBS™ 2.0

OPTIONS



STEALTH TECHNOLOGY™ HELPS CREATE A CONVERSATION-FRIENDLY ATMOSPHERE

The Stealth 895 NBS includes a sleek sound enclosure and proprietary airflow innovations that enable operation at the sound level of a normal conversation.

JARLESS BLENDING, THE FOREFRONT OF INNOVATION

Why waste ingredients when you can have amazingly proportioned drinks and smoothies blended right in the cup you give your customer? The Nitro Blending System minimizes waste, saves time, and increases your profit margin.

BUILT TO SAVE TIME AND MONEY

All Blendtec blenders are built to meet the unique needs of the commercial customer. Each feature—from top to bottom—delivers simple operation and is designed to reduce overall cost.










NBS MICRONIZING SYSTEM
BLENDS IN SECONDS
RIGHT FROM CUP TO CUSTOMER



NBS MICRONIZER
FITS MOST CUPS
PAPER OR PLASTIC



ULTRA HIGH-SPEED MOTOR
3.8 PEAK HP*
BLENDS THE TOUGHEST INGREDIENTS

 MOTOR	3.8 peak horsepower,* 120V / 220V available	
 INTERFACE	Illuminated OLED display with tactile keypad	
 SOUND ENCLOSURE	Fully enclosed, easy-to-clean blending station. Advanced sound enclosure helps blender operate at the sound level of normal conversation.	
 PROGRAM CYCLES	42 Preprogrammed blend cycles, including 2 for the NBS attachment, create custom or update included blend cycles via Blendtec's Blend Wizard™ online tool	
 USAGE	Recommended daily blends: 200	
 DIMENSIONS	H: 17.3" (43.9 cm) D: 9.0" (22.9 cm) W: 8.6" (21.8 cm)	H: 9.5" (24.1 cm) D: 4.25" (10.8 cm) W: 5" (12.7 cm)
 WEIGHT	15.8 lbs (7.2 kg)	15 oz (425 g)
 CERTIFICATIONS	Conforms to applicable UL and CSA safety standards as well as NSF sanitation standards.	

WARRANTY



*For international warranty and certification details please see your in-country distributor. *Peak Horsepower Achieved Under Laboratory Conditions
WWW.BLENDETEC.COM/COMMERCIAL | 1-800-BLENDETEC
SPS-051 A02, SPEC SHEET, STEALTH 895, US ENG, JAN 2019

