

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

### C-1FE 29" Single Solid Door Reach-In Freezer



#### FEATURES

- Stainless steel interior and exterior
- Aluminum back
- Refrigeration system keeps food at safe temperatures
- Self-closing doors with 90 degree stay-open feature
- Locks and keys included
- Adjustable heavy-duty PVC coated shelves
- Recessed door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- Removable installation board
- Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
  - ETL Sanitation Listed
- Conforms to UL & NSF Standards



**U**SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

### TECHNICAL DATA

#### DIMENSIONS

Exterior Dimensions	29"W x 32.2"D x 81.5"H
Interior Dimensions	24.4"W x 27"D x 59.5"H
Packaging Dimensions	30.3"W x 34"D x 84.5"H
Net Volume	20.6 cu. ft.
Unit Weight	306 lb.
Shipping Weight	346 lb.

#### ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	2.62
Plug Type	NEMA 5-15P
Power Cord Length	96"

#### COOLING

Temperature Range	-8°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	2/3

#### CONSTRUCTION

Exterior Material	430 Stainless Steel
Interior Material	430 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	3 Qty: 23.62"W x 23.23"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	90 lb.
Adjustable Shelf	Yes
Interior Light	Yes
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

### TECHNICAL DRAWING

MODEL: C-1FE

MFR ITEM #: C-1FX



NEMA 5-15P

