Coldline MC58 58" White School Milk Cooler

FEATURES

- 304 stainless steel interior
- White-coated steel exterior
- Refrigeration system keeps food at safe temperatures
- Stainless steel lid and door with latch and lock
- Holds up to 16 crates
- Digital thermostat
- 33 - 40 degrees F temperature range
- Foamed-in-place polyurethane insulation
- Preinstalled heavy-duty casters with brakes
- Bottom floor drain
- Hydro-Carbon R290 refrigerant

Thanks to Coldline's commitment to the highest quality materials and reliable refrigeration systems, this milk cooler is durable, reliable, and attracts lower utility costs. The Coldline heavy duty milk cooler machine is an ideal addition to any cafeteria.

- cETLus Listed
- ETL Sanitation Listed

Conforms to UL & NSF Standards

USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

USR BRANDS

USR Brands, Inc.
Phone: 800-764-1172 | www.usrbrands.com | sales@usrbrands.com

Rev. 02-2023

Page 810

USR BRANDS® RESERVES THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT NOTICE

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	58"W x 30.62"D x 41.38"H
Interior Dimensions	54.38"W x 27"D x 25.75"H
Packaging Dimensions	60"W x 32"D x 46"H
Net Volume	22.8 cu. ft.
Capacity	16 crates (13" x 13" x 11") 10 crates (19" x 13" x 11")
Unit Weight	265 lb.
Shipping Weight	305 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	1.33
Plug Type	NEMA 5-15P

COOLING

|	
Temperature Range	32°F to 40°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/3

CONSTRUCTION

Exterior Material	Stainless Steel, White Coated Steel
Interior Material	304 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: MC58

MFR ITEM #:

NEMA 5-15P

58"

41.38"
40"
35.78"

比例 0.080

30.62"

5.5"

30"
31.18"